

## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 1 of 18 Print Date 05/19/2018

# SAFETY DATA SHEET

## GEON HTX ULTRA LA426CD WOOD

## **Section 1. Identification**

GHS product identifier : GEON HTX ULTRA LA426CD WOOD

Chemical name: MixtureCAS number: MixtureOther means of identification: VC10008069

**Product type** : solid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation)

CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or

accident).

## Section 2. Hazards identification

This mixture has not been evaluated as a whole for health effects. All ingredients are bound in a PVC polymer matrix and potential for hazardous exposure as shipped is minimal. PVC resin is manufactured from Vinyl Chloride Monomer (VCM). PVC resin manufacturers take special efforts to strip residual VCM from their resins. Residual VCM in the resin is typically below 8.5 ppm. However, VCM is a known carcinogen. The end-user (fabricator) should take necessary precautions (mechanical ventilation, local exhaust, respiratory protection, etc.) to protect employees from exposure to any vapors or dusts that may be released during heating or fabrication. See Sections 8 and 11 for special precautions. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : While this material is not considered hazardous by the OSHA Hazard

Communication Standard (29 CFR 1910.1200), this SDS contains valuable information critical to the safe handling and proper use of the product. This SDS should be retained and available for employees and

other users of this product.

Classification of the substance or

mixture

Not classified.

#### **GHS** label elements



## GEON HTX ULTRA LA426CD WOOD

Version Number 1.6 Page 2 of 18 Revision Date 05/17/2018 Print Date 05/19/2018

Signal word : No signal word.

**Hazard statements**: No known significant effects or critical hazards.

#### **Precautionary statements**

General:Not applicable.Prevention:Not applicable.Response:Not applicable.Storage:Not applicable.Disposal:Not applicable.Supplemental label elements:None known.Hazards not otherwise classified:None known.

# Section 3. Composition/information on ingredients

Substance/mixture: MixtureChemical name: MixtureOther means of identification: VC10008069

#### **CAS** number/other identifiers

Ingredient name	%	CAS number
Dibutyltin mercaptide	1 - 3	10584-98-2
Titanium dioxide	0.3 - 1	13463-67-7
Styrene	0 - 0.3	100-42-5

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Page 3 of 18 Revision Date 05/17/2018 Print Date 05/19/2018

#### Description of necessary first aid measures

**Eye contact**: Immediately flush eyes with plenty of water, occasionally lifting the

upper and lower eyelids. Check for and remove any contact lenses.

Get medical attention if irritation occurs.

**Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable

for breathing. Get medical attention if symptoms occur.

**Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated

clothing and shoes. Get medical attention if symptoms occur.

**Ingestion**: Wash out mouth with water. Remove victim to fresh air and keep at

rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by

medical personnel. Get medical attention if symptoms occur.

### Most important symptoms/effects, acute and delayed

#### **Potential acute health effects**

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist

immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without

suitable training.

See toxicological information (Section 11)

## Section 5. Firefighting measures



### **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 4 of 18 Print Date 05/19/2018

#### **Extinguishing media**

Suitable extinguishing media Unsuitable extinguishing media

In case of fire, use water spray (fog), foam, dry chemical or  $CO_2$ .

None known.

Specific hazards arising from the chemical

No specific fire or explosion hazard.

Hazardous thermal decomposition products

May emit Hydrogen Chloride (HCl). Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

halogenated compounds metal oxide/oxides

Special protective actions for firefighters Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any

personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and selfcontained breathing apparatus (SCBA) with a full face-piece operated

in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without

suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment.

**For emergency responders**: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

See also the information in "For non-emergency personnel".

**Environmental precautions**: Avoid dispersal of spilled material and runoff and contact with soil,

waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil

or air).

#### Methods and materials for containment and cleaning up

Small spill : Move containers from spill area. Vacuum or sweep up material and

place in a designated, labeled waste container. Dispose of via a

licensed waste disposal contractor.

Large spill : Move containers from spill area. Prevent entry into sewers, water



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 5 of 18 Print Date 05/19/2018

courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

#### Precautions for safe handling

Protective measures Advice on general occupational hygiene

- Put on appropriate personal protective equipment (see Section 8).
  - Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

# Section 8. Exposure controls/personal protection

#### **Control parameters**

#### Occupational exposure limits

Ingredient name	Exposure limits
Dibutyltin mercaptide	OSHA PEL (1993-06-30) as Sn
	PEL: Permissible Exposure Level 0.1 mg/m3
	NIOSH REL (1994-06-01) as Sn
	Time Weighted Average (TWA) 0.1 mg/m3
	OSHA PEL 1989 (1989-03-01) as Sn
	PEL: Permissible Exposure Level 0.1 mg/m3 Form: Organic.
	ACGIH TLV (1996-05-18) as Sn
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 0.1 mg/m3
	ACGIH TLV (1994-09-01) as Sn
	TLV-STEL: Threshold Limit Value - Short Time Exposure Level 0.2
	mg/m3



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 6 of 18 Print Date 05/19/2018

Ctrmono	OSHA PEL 1989 (1989-03-01)
Styrene	PEL: Permissible Exposure Level 215 mg/m3 50 ppm
	Short-term exposure limit (STEL). A limit value beyond which
	there should be no exposure and which refers to a period of fifteen
	minutes, unless otherwise stated. 425 mg/m3 100 ppm
	OSHA PEL Z2 (1993-06-30)
	PEL: Permissible Exposure Level 100 ppm
	Ceiling-A concentration that should not be exceeded at any time
	during any part of the working day. 200 ppm
	Acceptable Maximum Peak (AMP) 600 ppm
	NIOSH REL (1994-06-01)
	Time Weighted Average (TWA) 215 mg/m3 50 ppm
	Short-term exposure limit (STEL). A limit value beyond which
	there should be no exposure and which refers to a period of fifteen
	minutes, unless otherwise stated. 425 mg/m3 100 ppm
	ACGIH TLV (1997-05-21)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 85 mg/m3 20 ppm
	TLV-STEL: Threshold Limit Value - Short Time Exposure Level
	170 mg/m3 40 ppm
Titanium dioxide	OSHA PEL 1989 (1989-03-01)
	PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust
	OSHA PEL (1993-06-30)
	PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust
	NIOSH REL (1994-06-01)
	ACGIH TLV (1996-05-18)
	TLV-TWA: Threshold Limit Value - Time weighted average PEL:
	Permissible Exposure Level 10 mg/m3

Appropriate engineering controls

Good general ventilation should be sufficient to control worker

exposure to airborne contaminants.

**Environmental exposure controls** 

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be

necessary to reduce emissions to acceptable levels.

## **Individual protection measures**



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 7 of 18 Print Date 05/19/2018

**Hygiene measures**: Wash hands, forearms and face thoroughly after handling chemical

products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used

when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a

higher degree of protection: safety glasses with side-shields.

**Skin protection** 

**Hand protection**: Chemical-resistant, impervious gloves complying with an approved

standard should be worn at all times when handling chemical products

if a risk assessment indicates this is necessary.

**Body protection**: Personal protective equipment for the body should be selected based

on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures

should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this

product.

**Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that

meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper

fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

#### **Appearance**

Physical state : solid [Pellets.]

Color : TAN

Odor Not available. **Odor threshold** Not available. Not available. pН **Melting point** Not available. **Boiling point** Not available. Flash point Not available. **Burning** time Not available. **Burning rate** Not available. **Evaporation rate** Not available. Flammability (solid, gas) Not available.



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Page 8 of 18 Revision Date 05/17/2018 Print Date 05/19/2018

Lower and upper explosive : Lower: Not available. (flammable) limits : Upper: Not available.

Vapor pressure: Not available.Vapor density: Not available.Relative density: Not available.Solubility: Not available.Solubility in water: Not available.Partition coefficient: n-: Not available.

octanol/water

Auto-ignition temperature: Not available.Decomposition temperature: Not available.SADT: Not available.

Viscosity : Dynamic: Not available.

Kinematic: Not available.

## Section 10. Stability and reactivity

**Reactivity** : No specific test data related to reactivity available for this product or

its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

Section 7).

Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will

not occur.

**Conditions to avoid** : Keep away from extreme heat and oxidizing agents.

Incompatible materials : Avoid contact with acetal homopolymers and acetyl homopolymers

during processing.

**Hazardous decomposition** 

products

: Under normal conditions of storage and use, hazardous decomposition

products should not be produced.

## Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Information on toxicological effects**

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Dibutyltin mercaptide				
	LD50 Oral	Rat	510 mg/kg	=
Remarks - Inhalation:	No applicable to	xicity data		
Remarks - Dermal:	No applicable to	xicity data		
Titanium dioxide	•	•		



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 9 of 18 Print Date 05/19/2018

Remarks - Oral:	No applicable toxicity data			
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Styrene				
	LD50 Oral	Rat	2,650 mg/kg	-
	LC50 Inhalation	Rat	2,770 ppm	4 h
	LC50 Inhalation	Rat	11.8 Mg/l	4 h
Remarks - Dermal:	No applicable toxic	city data		

Conclusion/Summary : Mixture.Not fully tested.

## Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium dioxide	Skin - Mild	Human		72 hrs	-
	irritant				
Styrene	Eyes - Mild	Human			-
	irritant				
	Skin - Mild	Rabbit			-
	irritant				
	Skin -	Rabbit			-
	Moderate				
	irritant				
	Eyes - Severe	Rabbit			-
	irritant				
	Eyes -	Rabbit		24 hrs	-
	Moderate				
	irritant				

Conclusion/Summary

Skin:Mixture.Not fully tested.Eyes:Mixture.Not fully tested.Respiratory:Mixture.Not fully tested.

## **Sensitization**

Conclusion/Summary

Skin: Mixture.Not fully tested.Respiratory: Mixture.Not fully tested.

**Mutagenicity** 

**Conclusion/Summary** : Mixture. Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture. Not fully tested.

9/18



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Page 10 of 18 Revision Date 05/17/2018 Print Date 05/19/2018

Classification

Product/ingredient	OSHA	IARC	NTP
name			
Titanium dioxide		2B	
Styrene		2B	

#### **Reproductive toxicity**

**Conclusion/Summary** : Mixture.Not fully tested.

**Teratogenicity** 

**Conclusion/Summary** : Mixture. Not fully tested.

### Specific target organ toxicity (single exposure)

Not available.

#### Specific target organ toxicity (repeated exposure)

Not available.

## **Aspiration hazard**

Not available.

Information on likely routes of

exposure

Not available.

#### Potential acute health effects

Eye contact: No known significant effects or critical hazards.Inhalation: No known significant effects or critical hazards.Skin contact: No known significant effects or critical hazards.Ingestion: No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

#### **Short term exposure**

**Potential immediate effects** : Not available.



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 11 of 18 Print Date 05/19/2018

**Potential delayed effects** : Not available.

**Long term exposure** 

Potential immediate effects : Not available.
Potential delayed effects : Not available.

**Potential chronic health effects** 

Conclusion/Summary : Mixture.Not fully tested.

General:No known significant effects or critical hazards.Carcinogenicity:No known significant effects or critical hazards.Mutagenicity:No known significant effects or critical hazards.Teratogenicity:No known significant effects or critical hazards.Developmental effects:No known significant effects or critical hazards.Fertility effects:No known significant effects or critical hazards.

## Numerical measures of toxicity

#### **Acute toxicity estimates**

Not available.

# Section 12. Ecological information

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
Dibutyltin mercaptide			
Remarks - Acute - Fish:	No applicable toxicity data		
Remarks - Acute - Aquatic	No applicable toxicity data		
invertebrates.:			
Remarks - Acute - Aquatic	No applicable toxicity data		
plants:			
Remarks - Chronic - Fish:	No applicable toxicity data		
Remarks - Chronic -	No applicable toxicity data		
Aquatic invertebrates.:			
Titanium dioxide			
	Acute LC50 > 1,000 Mg/l Marine	Fish - Fish	96 h
	water		
Remarks - Acute - Fish:	Acute		



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 12 of 18 Print Date 05/19/2018

		1	1	
	Acute LC50 3 Mg/l Fresh water	Aquatic invertebrates.	48 h	
		Crustaceans		
Remarks - Acute - Aquatic	Acute			
invertebrates.:			•	
	Acute LC50 6.5 Mg/l Fresh water	Aquatic invertebrates.	48 h	
		Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
Remarks - Acute - Aquatic	No applicable toxicity data			
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:				
Styrene				
	Acute LC50 4.02 Mg/l Fresh water	Fish - Fish	96 h	
Remarks - Acute - Fish:	Acute	_	_	
	Acute EC50 0.0047 Mg/l Fresh	Aquatic invertebrates.	48 h	
	water	Daphnia		
Remarks - Acute - Aquatic	Acute			
invertebrates.:				
	Acute LC50 52 Mg/l Marine water	Aquatic invertebrates. Crustaceans	48 h	
Remarks - Acute - Aquatic	Acute	•		
invertebrates.:				
	Acute EC50 1.4 Mg/l Fresh water	Aquatic plants - Algae	72 h	
Remarks - Acute - Aquatic	Acute			
plants:				
•	Acute EC50 0.72 Mg/l Fresh water	Aquatic plants - Algae	96 h	
Remarks - Acute - Aquatic	Acute		•	
plants:				
•	Acute NOEC 0.063 Mg/l Fresh	Aquatic plants - Algae	96 h	
	water			
Remarks - Acute - Aquatic	Chronic	•	•	
plants:				
Remarks - Chronic - Fish:	No applicable toxicity data			
Remarks - Chronic -	No applicable toxicity data			
Aquatic invertebrates.:	11			
GEON HTX ULTRA LA426C	D WOOD			
Remarks - Acute - Aquatic	Chemicals are not readily available a	s they are bound within the	e polymer matrix.	
invertebrates.:		•		
	ı			

Conclusion/Summary

: Chemicals are not readily available as they are bound within the polymer matrix.

## Persistence and degradability



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Page 13 of 18 Revision Date 05/17/2018 Print Date 05/19/2018

**Conclusion/Summary** : Chemicals are not readily available as they are bound within the

polymer matrix.

**Conclusion/Summary**: Chemicals are not readily available as they are bound within the

polymer matrix.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
8-Oxa-3,5-dithia-4-	3.4	-	low
stannatetradecanoic acid, 4,4-dibutyl-			
10-ethyl-7-oxo-, 2-ethylhexyl ester			
Benzene, ethenyl-	0.35	13.49	low

#### **Mobility in soil**

Soil/water partition coefficient

(KOC)

Other adverse effects

Not available.

No known significant effects or critical hazards.

# Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

## Section 14. Transport information



### **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Page 14 of 18 Revision Date 05/17/2018 Print Date 05/19/2018

U.S.DOT 49CFR Ground/Air/Water : Not regulated for transportation.

International Air ICAO/IATA

: Consult mode specific transport rules

International Water

IMO/IMDG

: Consult mode specific transport rules

# Section 15. Regulatory information

U.S. Federal regulations

: United States - TSCA 12(b) - Chemical export notification: None

of the components are listed.

United States - TSCA 4(a) - Final Test Rules: Not listed United States - TSCA 4(a) - ITC Priority list: Not listed United States - TSCA 4(a) - Proposed test rules: Not listed United States - TSCA 4(f) - Priority risk review: Not listed United States - TSCA 5(a)2 - Final significant new use rules: Not

listed

United States - TSCA 5(a)2 - Proposed significant new use rules:

Not listed

United States - TSCA 5(e) - Substances consent order: Not listed United States - TSCA 6 - Final risk management: Not listed United States - TSCA 6 - Proposed risk management: Not listed United States - TSCA 8(a) - Chemical risk rules: Not listed United States - TSCA 8(a) - Dioxin/Furane precusor: Not listed United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not

determined

United States - TSCA 8(a) - Preliminary assessment report

(PAIR): Listed Cyclohexene, 4-ethenyl-

United States - TSCA 8(c) - Significant adverse reaction (SAR):

Not listed

United States - TSCA 8(d) - Health and safety studies: Not listed United States - EPA Clean water act (CWA) section 307 - Priority

pollutants: Listed Vinyl chloride monomer

Acrylonitrile Ethyl benzene

Nickel antimony yellow rutile (C.I. Pigment Yellow 53)

United States - EPA Clean water act (CWA) section 311 -

Hazardous substances: Listed



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018

Page 15 of 18 Print Date 05/19/2018

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Flammable substances: Not listed

United States - EPA Clean air act (CAA) section 112 - Accidental

release prevention - Toxic substances: Not listed

**United States - Department of commerce - Precursor chemical:** 

Not listed

Clean Air Act Section 112(b)

Hazardous Air Pollutants (HAPs)

Clean Air Act Section 602 Class I

**Substances** 

Clean Air Act Section 602 Class II

**Substances** 

**DEA List I Chemicals (Precursor** 

Chemicals)

**DEA List II Chemicals (Essential** 

Chemicals)

Listed

Not listed

Not listed

Not listed

Not listed

#### US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

#### SARA 311/312

Classification Not applicable.

#### **Composition/information on ingredients**

Name	%	Classification
Dibutyltin mercaptide	1 - 3	АН
Titanium dioxide	0.3 - 1	СН
Styrene	0 - 0.3	F, AH, CH

#### **SARA 313**

	Product name	CAS number	%
Form R - Reporting	Nickel antimony yellow	8007-18-9	1 - 3
requirements	rutile (C.I. Pigment Yellow		
	53)		
	Styrene	100-42-5	0 - 0.3
Supplier notification	Nickel antimony yellow rutile (C.I. Pigment Yellow 53)	8007-18-9	1 - 3



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Page 16 of 18 Revision Date 05/17/2018 Print Date 05/19/2018

Styrene 100-42-5 0 - 0.3

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

**State regulations** 

MassachusettsNone of the components are listed.New YorkThe following components are listed:

Styrene

**New Jersey** : The following components are listed:

Styrene

Ethene, chloro-, homopolymer

Nickel antimony yellow rutile (C.I. Pigment Yellow 53)

Titanium dioxide

**Pennsylvania** : The following components are listed:

Titanium dioxide

Styrene

Nickel antimony yellow rutile (C.I. Pigment Yellow 53)

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

**United States inventory (TSCA 8b)** : All components are listed or exempted.

**Canada inventory** : All components are listed or exempted.

**International regulations** 

**Inventory list** 

Australia : Not determined.

**Canada** : All components are listed or exempted.

China Not determined. **Europe inventory** Not determined. Japan Not determined. **New Zealand** Not determined. **Philippines** Not determined. Republic of Korea Not determined. **Taiwan** Not determined. **Turkey** Not determined.

United States : All components are listed or exempted.



### GEON HTX ULTRA LA426CD WOOD

Version Number 1.6 Page 17 of 18 Revision Date 05/17/2018 Print Date 05/19/2018

## Section 16. Other information

#### **Hazardous Material Information System (U.S.A.)**

Health	/	0
Flammability		0
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

History

Date of printing: 05/19/2018Date of issue/Date of revision: 05/17/2018Date of previous issue: 04/02/2018

Version : 1.6

**Key to abbreviations**: ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine

pollution)

UN = United Nations

**References** : Not available.

#### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.



## **GEON HTX ULTRA LA426CD WOOD**

Version Number 1.6 Revision Date 05/17/2018 Page 18 of 18 Print Date 05/19/2018