MATERIAL SAFETY DATA SHEET **GEON X15517402701**

Version Number 1.0 Revision Date 04/25/2012

Page 1 of 7 Print Date 8/26/2012

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone | : | 1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|----------------------------------|---|--|
| Product name | : | GEON X15517402701 |
| Product code | : | VC10008449 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |
| Product Use | : | Industrial Applications |

2. COMPOSITION/INFORMATION ON REGULATED INGREDIENTS

| Components | CAS-No. | Weight percent |
|-------------------|-----------|----------------|
| Calcium stearate | 1592-23-0 | 1 - 5 |
| Calcium carbonate | 471-34-1 | 1 - 5 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

| : Inhalation, Ingestion, Skin contact |
|---|
| |
| : Resin particles, like other inert materials, can be mechanically irritating. |
| : May be harmful if swallowed. |
| : Resin particles, like other inert materials, are mechanically irritating to eyes. |
| : Experience shows no unusual dermatitis hazard from routine handling. |
| : Refer to Section 11 for Toxicological Information. |
| |

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON X15517402701**

Version Number 1.0 Revision Date 04/25/2012 Page 2 of 7 Print Date 8/26/2012

| Medical Conditions Aggravated by Exposure: | : None known. |
|--|---|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. |
| | 5. FIRE-FIGHTING MEASURES |
| Flash point | : not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media | not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. |
| Special Fire Fighting Procedures | : Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne contaminants. |
| Unusual Fire/Explosion Hazards | : May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods. |
| | 7. HANDLING AND STORAGE |

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON X15517402701**

| | Page 3 of 7 Print Date 8/26/2012 |
|------|---|
| | |
| : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. |
| : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. |
| POSU | RE CONTROLS/PERSONAL PROTECTION |
| : | No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection. |
| : | Safety glasses with side-shields |
| : | Protective gloves |
| : | Long sleeved clothing |
| : | Safety shoes |
| : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels. |
| : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |
| | |
| | |
| | |
| | |
| | |
| | : : : |

MATERIAL SAFETY DATA SHEET **GEON X15517402701**

Version Number 1.0 Revision Date 04/25/2012 Page 4 of 7 Print Date 8/26/2012

| Components | Value | Exposure time | Exposure type | List: |
|---------------------------|----------|-----------------------------------|----------------------|----------|
| Calcium stearate | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| Calcium carbonate 5 mg/m3 | | Recommended exposure limit (REL): | Respirable. | NIOSH |
| | 10 mg/m3 | Recommended exposure limit (REL): | Total | NIOSH |
| | 5 mg/m3 | PEL: | Respirable fraction. | OSHA Z1 |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 5 mg/m3 | Time Weighted Average (TWA): | Respirable fraction. | OSHA Z1A |
| | 15 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A |
| | 10 mg/m3 | Time Weighted Average (TWA): | | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 pellets, powder
 BLACK
 very faint
 Not determined
 not applicable
 insoluble
- Evaporation rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable

10. STABILITY AND REACTIVITY

Stability Stable : Hazardous Polymerization Will not occur. : Conditions to avoid Keep away from oxidizing agents and open flame. To avoid thermal : decomposition, do not overheat. Incompatible Materials Incompatible with strong acids and oxidizing agents., Avoid contact : with acetal homopolymers and acetal copolymers during processing. Hazardous decomposition Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen : products (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

4/7

MATERIAL SAFETY DATA SHEET **GEON X15517402701**

Version Number 1.0 Revision Date 04/25/2012 Page 5 of 7 Print Date 8/26/2012

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|----------|-------------------|----------|--------------|
| 471-34-1 | Calcium carbonate | Irritant | Eyes, Skin. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|-------------------|-----------|------------|-------------|
| 1592-23-0 | Calcium stearate | Oral LD50 | > 10 gm/kg | rat |
| 471-34-1 | Calcium carbonate | Oral | 6,450 | ratratmouse |
| | | LD50Oral | mg/kg6,450 | |
| | | LD50Oral | mg/kg6,450 | |
| | | LD50 | mg/kg | |

12. ECOLOGICAL INFORMATION

| Persistence and degradability | : | Not readily biodegradable. |
|----------------------------------|---|--|
| Environmental Toxicity | : | Adverse ecological impact is not known or expected under normal use. |
| Bioaccumulation Potential | : | no data available |

Additional advice : not applicable

13. DISPOSAL CONSIDERATIONS Product : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. Contaminated packaging : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification

material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

14. TRANSPORT INFORMATION

| U.S. DOT Classification | : | Not regulated for transportation. |
|-------------------------|---|-----------------------------------|
| ICAO/IATA | : | Not regulated for transportation. |
| IMO/IMDG (maritime) | : | Not regulated for transportation. |

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **GEON X15517402701**

Version Number 1.0 Revision Date 04/25/2012

Page 6 of 7 Print Date 8/26/2012

| | 15. REGULATORY INFORMATION |
|----------------------------------|--|
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. |
| US. EPA CERCLA Hazardous | Substances (40 CFR 302) |
| not applicable | |
| | |
| California Proposition 65 | : Not applicable |
| SARA Title III Section 302 Ex | tremely Hazardous Substance |
| Unless specific chemicals are id | dentified under this section, this product is Not Applicable under this regulation |
| | |
| SARA Title III Section 313 To | xic Chemicals: |
| Unless specific chemicals are id | dentified under this section, this product is Not Applicable under this regulation |
| Canadian Regulations: | |
| National Pollutant Relea | ise Inventory (NPRI) |
| not applicable | |
| WHMIS Classification | : Not controlled. |
| DSL | : All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt. |
| National Inventories: | |
| Australia AICS | : Listed |
| China IECS | : Listed |
| Europe EINECS | : Listed |
| Japan ENCS | : Not determined |
| | |

PolyOne

MATERIAL SAFETY DATA SHEET **GEON X15517402701**

Version Number 1.0 Revision Date 04/25/2012 Page 7 of 7 Print Date 8/26/2012

Korea KECI : Listed

Philippines PICCS : Listed

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.