MATERIAL SAFETY DATA SHEET **16740-02 EXPM5110 GRAY 2448**

Version Number 1.1 Revision Date 10/29/2013 Page 1 of 7 Print Date 10/29/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	16740-02 EXPM5110 GRAY 2448
Product code	:	VC10008669
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium stearate	1592-23-0	1 - 5
Titanium dioxide	13463-67-7	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact
: Resin particles, like other inert materials, can be mechanically irritating.
: May be harmful if swallowed.
: Resin particles, like other inert materials, are mechanically irritating to eyes.
: Experience shows no unusual dermatitis hazard from routine handling.
: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET **16740-02 EXPM5110 GRAY 2448**

Version Number 1.1 Revision Date 10/29/2013 Page 2 of 7 Print Date 10/29/2013

Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit: not applicable not applicableAuto-ignition temperature Suitable extinguishing media: Not applicableSpecial Fire Fighting Procedures: Fullface self-contained breathing apparatus (SCBA) used in pressure mode should be worn to prevent inhalation of airbo contaminants.Unusual Fire/Explosion Hazards: May emit Hydrogen Chloride (HCl) or Carbon Monoxide (G oxides of nitrogen (NOx), other hazardous materials, and sr all possible.	
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE

PolyOne.

MATERIAL SAFETY DATA SHEET **16740-02 EXPM5110 GRAY 2448**

	Print Date 10/29/20
:	Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
OSU	RE CONTROLS/PERSONAL PROTECTION
:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
:	Safety glasses with side-shields
:	Protective gloves
:	Long sleeved clothing
:	Safety shoes
:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
	: 05U : : : :

PolvOne.

MATERIAL SAFETY DATA SHEET 16740-02 EXPM5110 GRAY 2448

Version Number 1.1 Revision Date 10/29/2013

Page 4 of 7 Print Date 10/29/2013

Components	Value	Exposure time	Exposure type	List:
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):		ACGIH
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):	as Ti	MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):	as Ti	MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : pellets, powder: GREY: very faint: Not determined

: not applicable

: insoluble

: solid

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH

- Not applicableNot determinedNot establishednot applicable
- : not applicable
- : not applicable

10. STABILITY AND REACTIVITY

Stability	The product is stable i	f stored and handled as prescribed.
Hazardous Polymerization	Will not occur.	
Conditions to avoid	Keep away from oxidi decomposition, do not	zing agents and open flame. To avoid thermal overheat.
Incompatible Materials	1	ong acids and oxidizing agents., Avoid contact ners and acetal copolymers during processing.
Hazardous decomposition products	(NOx), other hazardou Prolonged heating (ap (200 °C) or short term	b, carbon monoxide (CO), oxides of nitrogen as materials, and smoke are all possible. proximately 30 minutes or more) above 392 °F heating at 482 °F (250 °C) may result in and evolution of carbon monoxide and

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

MATERIAL SAFETY DATA SHEET **16740-02 EXPM5110 GRAY 2448**

Version Number 1.1

Revision Date 10/29/2013

Page 5 of 7 Print Date 10/29/2013

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
13463-67-7	Titanium dioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	no data available
Additional advice	:	not applicable

13. DISPOSAL CONSIDERATIONS

: Like most thermoplastic plastics the product can be recycled. When possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne

MATERIAL SAFETY DATA SHEET **16740-02 EXPM5110 GRAY 2448**

Version Number 1.1 Revision Date 10/29/2013

Page 6 of 7 Print Date 10/29/2013

U.S. DOT Classification	: Not regulated for transportation.				
ICAO/IATA	: Not regulated for transportation.				
IMO/IMDG (maritime)	: Not regulated for transportation.				
15. REGULATORY INFORMATION					
US Regulations:					
OSHA Status	: Classified as hazardous based on components.				
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.				
US. EPA CERCLA Hazardous Substances (40 CFR 302)					
not applicable					
California Propositio 65	n : Not applicable				
SARA Title III Section 302 Extremely Hazardous Substance					
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation					
SARA Title III Section 313 Toxic Chemicals:					
Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation					
Canadian Regulations:					
National Pollutant Release Inventory (NPRI)					
not applicable					
WHMIS Classification	on : D2A				
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.				
	Substances East (BSE) of the exempt.				
National Inventories:					

PolyOne

MATERIAL SAFETY DATA SHEET 16740-02 EXPM5110 GRAY 2448

Version Number 1.1 Revision Date 10/29/2013 Page 7 of 7 Print Date 10/29/2013

		16. OTHER INFORMATION
Philippines PICCS	:	Not determined
Korea KECI	:	Not determined
Japan ENCS	:	Not determined
Europe EINECS	:	Listed
China IECS	:	Not determined

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in

combination with any other materials or in any process, unless specified in the text.