# MATERIAL SAFETY DATA SHEET 16875-03 EXPA7D01 YELLOW

Version Number 1.0 Revision Date 05/15/2013 Page 1 of 7 Print Date 5/16/2013

#### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	16875-03 EXPA7D01 YELLOW
Product code	:	VC10009297
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
8-Oxa-3,5-dithia-4-stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7-oxo-, 2-ethylhexyl ester	57583-35-4	1 - 5
Stannane, methyltris(2- ethylhexyloxycarbonylmethylthio)-	57583-34-3	1 - 5

## **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	:	Inhalation, Ingestion, Skin contact
Acute exposure		
Inhalation	:	Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	:	May be harmful if swallowed.
Eyes	:	Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	:	Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

# MATERIAL SAFETY DATA SHEET **16875-03 EXPA7D01 YELLOW**

Version Number 1.0 Revision Date 05/15/2013 Page 2 of 7 Print Date 5/16/2013

Medical Conditions Aggravated by Exposure:	: None known.	
	4. FIRST AID MEASURES	
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases doubt seek medical advice.	of
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for least 15 minutes. If eye irritation persists, seek medical attention.	at
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
	5. FIREFIGHTING MEASURES	
Flash point	: not applicable	
Flammable Limits		
Upper explosion limit	: not applicable	
Lower explosion limit	: not applicable	
Auto-ignition temperature	: Not applicable	
Suitable extinguishing media	: Carbon dioxide blanket, Water spray, Dry powder, Foam.	
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positiv pressure mode should be worn to prevent inhalation of airborne	e
Unusual Fire/Explosion Hazards	<ul> <li>contaminants.</li> <li>May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) und fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> </ul>	
	5. ACCIDENTAL RELEASE MEASURES	
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	: Should not be released into the environment. The product should n be allowed to enter drains, water courses or the soil.	ot
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.	1

PolyOne.

# MATERIAL SAFETY DATA SHEET 16875-03 EXPA7D01 YELLOW

Version Number 1.0 Revision Date 05/15/2013 Page 3 of 7 Print Date 5/16/2013

	7. HANDLING	AND STORAGE			
Handling	only in areas with condensates ma	to prevent the build up of electrostatic charge. Heat th appropriate exhaust ventilation. Processing fume y contain combustible or toxic residue. Periodically cts, and other surfaces to minimize accumulation of			
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. EX	POSURE CONTROLS	PERSONAL PROTECTION			
Respiratory protection		piratory protective equipment normally required. If soccur wear appropriate respiratory protection.			
Eye/Face Protection	: Safety glasses v	vith side-shields			
Hand protection	: Protective glove	s			
Skin and body protection	: Long sleeved cl	othing			
Additional Protective Measures	: Safety shoes				
General Hygiene Considerations	practice. Wash product may co number 75-01-4 normal working exposure limits user should take ventilation, loca protection, etc.) VCM or dusts t	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.			
Engineering measures	•	as with appropriate exhaust ventilation. Provide aust ventilation at machinery.			
Exposure limit(s)					
9	PHYSICAL AND CH	EMICAL PROPERTIES			
Form	: solid	Evapouration rate : Not applicable			
Appearance Colour	: pellets, powder : YELLOW	Specific Gravity:Not determinedBulk density:Not established			

# MATERIAL SAFETY DATA SHEET **16875-03 EXPA7D01 YELLOW**

: very faint

Version Number 1.0 Revision Date 05/15/2013

Odour

\_

Melting point/range Boiling Point: Water solubility	: Not determined Vapour density : not applicable : not applicable pH : not applicable : insoluble
	10. STABILITY AND REACTIVITY
Stability	: The product is stable if stored and handled as prescribed.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

## **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
57583-35-4	8-Oxa-3,5-dithia-4- stannatetradecanoic acid, 10-ethyl-4,4-dimethyl-7- oxo-, 2-ethylhexyl ester	Irritant	Eyes, Skin.
57583-34-3	Stannane, methyltris(2- ethylhexyloxycarbonylmet hylthio)-	Irritant	Eyes, Skin.

### LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
57583-34-3	Stannane, methyltris(2- ethylhexyloxycarbonylmet hylthio)-	Oral LD50	920 mg/kg	rat

### **12. ECOLOGICAL INFORMATION**

Page 4 of 7 Print Date 5/16/2013

: not applicable

PolyOne

Vapour pressure

PolyOne.

# MATERIAL SAFETY DATA SHEET **16875-03 EXPA7D01 YELLOW**

Version Number 1.0 Revision Date 05/15/2013 Page 5 of 7 Print Date 5/16/2013

: Not readily biodegradable.
: Adverse ecological impact is not known or expected under normal use.
: no data available
: not applicable
13. DISPOSAL CONSIDERATIONS
: Like most thermoplastic plastics the product can be recycled. Wh possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
14. TRANSPORT INFORMATION
: Not regulated for transportation.
: Not regulated for transportation.
: Not regulated for transportation.
15. REGULATORY INFORMATION
: Classified as hazardous based on components.
: All components of this product are listed on or exempt from the TSCA Inventory.
ubstances (40 CFR 302)
: Not applicable

# MATERIAL SAFETY DATA SHEET 16875-03 EXPA7D01 YELLOW

Version Number 1.0 Revision Date 05/15/2013 Page 6 of 7 Print Date 5/16/2013

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

Canadian Regulations:

National Pollutant Release Inventory (NPRI)

Chemical Name	CAS-No.	Weight	NPRI ID#
		percent	
Bis (2-ethylhexyl) adipate	103-23-1	5.00 - 10.00	

WHMIS Classification : D2B

WHMIS Ingredient Disclosure List

CAS-No.	
103-23-1	
57583-34-3	

DSL

DSL status has not been determined. Quantity use in Canada may be restricted by regulations.

National Inventories:

ot determined
ot determined
isted
ot determined
ot determined
ot determined

:

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The

PolyOne.

# MATERIAL SAFETY DATA SHEET 16875-03 EXPA7D01 YELLOW

Version Number 1.0 Revision Date 05/15/2013 Page 7 of 7 Print Date 5/16/2013

information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.