PolvOne

MATERIAL SAFETY DATA SHEET 16908-01 EXPCP8000 NATURAL

Version Number 1.0 Revision Date 07/10/2013 Page 1 of 6 Print Date 7/10/2013

1. PRODUCT AND COMPANY IDENTIFICATION POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012		
Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	16908-01 EXPCP8000 NATURAL
Product code	:	VC10009391
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent	
Calcium carbonate	1317-65-3	10 - 30	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

: Inhalation, Ingestion, Skin contact
: Resin particles, like other inert materials, can be mechanically irritating.
: May be harmful if swallowed.
: Resin particles, like other inert materials, are mechanically irritating to eyes.
: Experience shows no unusual dermatitis hazard from routine handling.
: Refer to Section 11 for Toxicological Information.

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 16908-01 EXPCP8000 NATURAL

Version Number 1.0 Revision Date 07/10/2013 Page 2 of 6 Print Date 7/10/2013

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET 16908-01 EXPCP8000 NATURAL

sion Number 1.0 /ision Date 07/10/2013			Print	Page 3 of Date 7/10/201
	c c	nly in areas with appropriate en ondensates may contain combu lean hoods, ducts, and other su nese materials.	stible or toxic residue.	Periodically
Storage		Leep containers dry and tightly nd contamination. Keep in a d		e absorption
8.	EXPOSURE	CONTROLS/PERSONAL	PROTECTION	
Respiratory protection		No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.		
Eye/Face Protection	: S	afety glasses with side-shields		
Hand protection	: P	rotective gloves		
Skin and body protection	: L	ong sleeved clothing		
Additional Protective Measures	: S	afety shoes		
General Hygiene Considerations	p n n e u v v V	Iandle in accordance with good ractice. Wash hands before br roduct may contain residual vi umber 75-01-4) below 8.5 ppn ormal working conditions with xposure limits will be exceeded ser should take the necessary p entilation, local exhaust ventila rotection, etc.) to ensure airbon /CM or dusts that may be relea elow regulated levels.	eaks and at the end of we nyl chloride monomer (V n (0.00085%). It is unlik a dequate ventilation, th d for residual VCM. How precautions (e.g. mechan ation, air-monitoring, res- rne levels of any vapors	orkday. This VCM) (CAS ely, under iat the wever, the ical spiratory including
Engineering measures		leat only in areas with appropr ppropriate exhaust ventilation		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
 	20 / 2			MV OFI

 20 mg/m3
 Short Term Exposure Limit (STEL):
 MX OEL

9. PHYSICAL AND CHEMICAL PROPERTIES

PolyOne

MATERIAL SAFETY DATA SHEET 16908-01 EXPCP8000 NATURAL

Version Number 1.0 Revision Date 07/10/2013

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility	 solid pellets, powder NO PIGMENT very faint Not determined not applicable insoluble 	Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH	: Not established : not applicable
	10. STABILITY ANI	D REACTIVITY	
Stability	: The product is stab	le if stored and handled as	prescribed.
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from or decomposition, do	xidizing agents and open flands overheat.	ame. To avoid thermal
Incompatible Materials	-	strong acids and oxidizing plymers and acetal copolyn	-
Hazardous decomposition products	(NOx), other hazar Prolonged heating (200 °C) or short te	D2), carbon monoxide (CO dous materials, and smoke (approximately 30 minutes erm heating at 482 °F (250 tion and evolution of carbo	are all possible. or more) above 392 °F °C) may result in

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory
			system.

12. ECOLOGICAL INFORMATION

Persistence and degradability	:	Not readily biodegradable.
Environmental Toxicity	:	Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	:	no data available
Additional advice	:	not applicable

PolyOne.

MATERIAL SAFETY DATA SHEET 16908-01 EXPCP8000 NATURAL

Version Number 1.0 Revision Date 07/10/2013 Page 5 of 6 Print Date 7/10/2013

	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO/IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardo	us Substances (40 CFR 302)
not applicable	
California Propositio 65	n : Not applicable
SARA Title III Section 302	Extremely Hazardous Substance
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regula
SARA Title III Section 313	Foxic Chemicals:

MATERIAL SAFETY DATA SHEET 16908-01 EXPCP8000 NATURAL

Version Number 1.0 Revision Date 07/10/2013 Page 6 of 6 Print Date 7/10/2013

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation Canadian Regulations: National Pollutant Release Inventory (NPRI) NPRI ID# Chemical Name CAS-No. Weight percent Bis (2-ethylhexyl) adipate 103-23-1 10.00 - 30.00 WHMIS Classification : Not controlled. DSL All components of this product are on the Canadian Domestic : Substances List (DSL) or are exempt. National Inventories: Australia AICS Not determined : China IECS Not determined : Europe EINECS Listed : Japan ENCS : Not determined Korea KECI Not determined : **Philippines PICCS** Not determined :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.