MATERIAL SAFETY DATA SHEET RTMB (5.2% Blue 5006 UMB) FDA 405A

Version Number 1.1 Revision Date 12/19/2013

Page 1 of 6 Print Date 12/19/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	RTMB (5.2% Blue 5006 UMB) FDA 405A
Product code	:	VC10009673
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.
Chronic exposure	: Refer to Section 11 for Toxicological Information.

PolyOne.

MATERIAL SAFETY DATA SHEET RTMB (5.2% Blue 5006 UMB) FDA 405A

Version Number 1.1 Revision Date 12/19/2013 Page 2 of 6 Print Date 12/19/2013

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.
	5. FIREFIGHTING MEASURES
Flash point	: not applicable
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.
	7. HANDLING AND STORAGE
Handling	: Take measures to prevent the build up of electrostatic charge. Heat

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET *RTMB (5.2% Blue 5006 UMB) FDA 405A*

Version Number 1.1 Revision Date 12/19/2013	Page 3 of 6 Print Date 12/19/2013
Storage :	only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXPOSU	IRE CONTROLS/PERSONAL PROTECTION
Respiratory protection :	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection :	Safety glasses with side-shields
Hand protection :	Protective gloves
Skin and body protection :	Long sleeved clothing
Additional Protective : Measures	Safety shoes
General Hygiene : Considerations	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures :	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)	
	nponents above regulatory thresholds in this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- solid
 pellets, powder
 BLUE
 very faint
 Not determined
 not applicable
 insoluble
- Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH
- Not applicable
 Not determined
 Not established
 not applicable
 not applicable
 not applicable

PolyOne

MATERIAL SAFETY DATA SHEET *RTMB (5.2% Blue 5006 UMB) FDA 405A*

Version Number 1.1 Revision Date 12/19/2013

Page 4 of 6 Print Date 12/19/2013

 The product is stable if stored and handled as prescribed. Will not occur. Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
: Keep away from oxidizing agents and open flame. To avoid thermal
: Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °I (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.
11. TOXICOLOGICAL INFORMATION
components above regulatory thresholds in this product.
12. ECOLOGICAL INFORMATION
: Not readily biodegradable.
: Adverse ecological impact is not known or expected under normal use.
: no data available
: not applicable
13. DISPOSAL CONSIDERATIONS
: Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.

PolyOne.

MATERIAL SAFETY DATA SHEET RTMB (5.2% Blue 5006 UMB) FDA 405A

Version Number 1.1 Revision Date 12/19/2013 Page 5 of 6 Print Date 12/19/2013

U.S. DOT Classification	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO/IMDG (maritime)	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on or exempt from the TSCA Inventory.
US. EPA CERCLA Hazardou	us Substances (40 CFR 302)
not applicable	
California Propositior 65	n : Not applicable
SARA Title III Section 302 E	Extremely Hazardous Substance
Unless specific chemicals are	e identified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 T	
	Foxic Chemicals:
	Foxic Chemicals:
Unless specific chemicals are Canadian Regulations:	Foxic Chemicals:
Unless specific chemicals are Canadian Regulations:	Foxic Chemicals: e identified under this section, this product is Not Applicable under this regulation
Unless specific chemicals are Canadian Regulations: National Pollutant Rel	Foxic Chemicals: e identified under this section, this product is Not Applicable under this regulation lease Inventory (NPRI)
Unless specific chemicals are Canadian Regulations: National Pollutant Rel not applicable	Foxic Chemicals: e identified under this section, this product is Not Applicable under this regulation lease Inventory (NPRI)
Unless specific chemicals are Canadian Regulations: National Pollutant Rel not applicable WHMIS Classificatio	Foxic Chemicals: e identified under this section, this product is Not Applicable under this regulation lease Inventory (NPRI) on : Not controlled. : All components of this product are on the Canadian Domestic

PolyOne

MATERIAL SAFETY DATA SHEET RTMB (5.2% Blue 5006 UMB) FDA 405A

Version Number 1.1 Revision Date 12/19/2013 Page 6 of 6 Print Date 12/19/2013

	16 OTHER INFORMATION	
Philippines PICCS	: Listed	
Korea KECI	: Listed	
Japan ENCS	: Listed	
Europe EINECS	: Listed	
China IECS	: Listed	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.