PolvOne

MATERIAL SAFETY DATA SHEET **GEON M5240 BLACK (T1)**

Version Number 1.0 Revision Date 11/20/2013

Page 1 of 7 Print Date 11/21/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

Telephone Emergency telephone number	:	1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	GEON M5240 BLACK (T1)
Product code	:	VC10009701
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS-No.	Weight percent
Calcium stearate	1592-23-0	1 - 5
Carbon black	1333-86-4	1 - 5
Calcium carbonate	471-34-1	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON M5240 BLACK (T1)**

Version Number 1.0 Revision Date 11/20/2013 Page 2 of 7 Print Date 11/21/2013

Medical Conditions : None known. Aggravated by Exposure:				
	4. FIRST AID MEASURES			
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.			
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.			
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention.			
Skin	: Wash off with soap and plenty of water. If skin irritation persists seek medical attention.			
	5. FIREFIGHTING MEASURES			
Flash point	: not applicable			
Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion	 not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under the self of the			
Hazards	 fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. 6. ACCIDENTAL RELEASE MEASURES 			
	0. ACCIDENTAL RELEASE MEASURES			
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.			
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.			
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal.			

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON M5240 BLACK (T1)**

Version Number 1.0 Revision Date 11/20/2013 Page 3 of 7 Print Date 11/21/2013

Handling	:	Take measures to prevent the build up of electrostatic charge. Heat
	·	only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials.
Storage	:	Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.
8. EXI	POSU	RE CONTROLS/PERSONAL PROTECTION
Respiratory protection	:	No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection.
Eye/Face Protection	:	Safety glasses with side-shields
Hand protection	:	Protective gloves
Skin and body protection	:	Long sleeved clothing
Additional Protective Measures	:	Safety shoes
General Hygiene Considerations	:	Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.
Engineering measures	:	Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.
Exposure limit(s)		

P<u>olyOne</u>

MATERIAL SAFETY DATA SHEET GEON M5240 BLACK (T1)

Version Number 1.0 Revision Date 11/20/2013 Page 4 of 7 Print Date 11/21/2013

Components	Value	Exposure time	Exposure type	List:
Calcium stearate	10 mg/m3	Time Weighted Average (TWA):		ACGIH
Carbon black	3.5 mg/m3	Recommended exposure limit (REL):		NIOSH
	0.1 mg/m3	Recommended exposure limit (REL):		NIOSH
	3.5 mg/m3	PEL:		OSHA Z1
	3.5 mg/m3	Time Weighted Average (TWA):		OSHA Z1A
	3.5 mg/m3	Time Weighted Average (TWA):		MX OEL
	7 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	3 mg/m3	Time Weighted Average (TWA):	Inhalable fraction.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
	5 mg/m3	Time Weighted Average (TWA):	Respirable fraction.	OSHA Z1A
	15 mg/m3	Time Weighted Average (TWA):	Total dust.	OSHA Z1A
	10 mg/m3	Time Weighted Average (TWA):		MX OEL
	20 mg/m3	Short Term Exposure Limit (STEL):		MX OEL
	5 mg/m3	Recommended exposure limit (REL):	Respirable.	NIOSH
	10 mg/m3	Recommended exposure limit (REL):	Total	NIOSH

9. PHYSICAL AND CHEMICAL PROPERTIES

- Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility
- : solid : pellets, powder : BLACK : very faint : Not determined : not applicable : insoluble

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pН

: Not applicable : Not determined : Not established : not applicable :

- not applicable
- not applicable :

10. STABILITY AND REACTIVITY

Stability	:	The product is stable if stored and handled as prescribed.
Hazardous Polymerization	:	Will not occur.
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.

MATERIAL SAFETY DATA SHEET **GEON M5240 BLACK (T1)**

Version Number 1.0 Revision Date 11/20/2013 Page 5 of 7 Print Date 11/21/2013

Incompatible Materials	:	Incompatible with strong acids and oxidizing agents., Avoid contact with acetal homopolymers and acetal copolymers during processing.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 °F (200 °C) or short term heating at 482 °F (250 °C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1333-86-4	Carbon black	Systemic effects	Eyes, Respiratory system.
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1592-23-0	Calcium stearate	Oral LD50	> 10 gm/kg	rat
1333-86-4	Carbon black	Oral LD50	>15,400 mg/kg	rat
		Dermal LD50	> 3 gm/kg	rabbit
471-34-1	Calcium carbonate	Oral	6,450	ratratmouse
		LD50Oral	mg/kg6,450	
		LD50Oral	mg/kg6,450	
		LD50	mg/kg	

Additional Health Hazard Information:

Carbon black 1333-86-4 Carcinogenicity: Many inhalation toxicologists believe that the tumor response observed in the referenced rat studies is species specific and does not correlate to human exposure. However, the IARC evaluation in Monograph Volume 65, issued in April 1996 concluded that, "There is sufficient evidence in experimental animals for the carcinogenicity of carbon black". Based on this evaluation, along with their evaluation of inadequate evidence of carcinogenicity in humans, IARC's overall evaluation is that "Carbon Black is possibly carcinogenic to humans (Group 2B). The IARC 2B listing only pertains to airborne, unbound carbon black particles of respirable size. Carbon Black has not been listed as a carcinogen by the National Toxicology Program (NTP) or the Occupational Safety and Health Administration (OSHA). The National Institute of Occupational Safety and Health (NIOSH) criteria document on carbon black recommends that only carbon black with PAH (polynuclear aromatic hydrocarbon) levels greater than 0.1% be considered suspect carcinogens.

12. ECOLOGICAL INFORMATION

PolyOne.

MATERIAL SAFETY DATA SHEET **GEON M5240 BLACK (T1)**

Version Number 1.0 Revision Date 11/20/2013 Page 6 of 7 Print Date 11/21/2013

readily biodegradable. verse ecological impact is not known or expected under normal lata available applicable SPOSAL CONSIDERATIONS e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. ycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, sportation and disposal in accordance with applicable federal, e/provincial and local regulations.
lata available applicable SPOSAL CONSIDERATIONS e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. ycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, sportation and disposal in accordance with applicable federal,
applicable SPOSAL CONSIDERATIONS e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. ycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, sportation and disposal in accordance with applicable federal,
SPOSAL CONSIDERATIONS e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. ycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, sportation and disposal in accordance with applicable federal,
e most thermoplastic plastics the product can be recycled. Where sible recycling is preferred to disposal or incineration. The erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. ycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, sportation and disposal in accordance with applicable federal,
erator of waste material has the responsibility for proper waste sification, transportation and disposal in accordance with licable federal, state/provincial and local regulations. ycling is preferred when possible. The generator of waste erial has the responsibility for proper waste classification, sportation and disposal in accordance with applicable federal,
erial has the responsibility for proper waste classification, sportation and disposal in accordance with applicable federal,
RANSPORT INFORMATION
regulated for transportation.
regulated for transportation.
regulated for transportation.
GULATORY INFORMATION
ssified as hazardous based on components.
components of this product are listed on or exempt from the CA Inventory.
es (40 CFR 302)

PolyOne.

MATERIAL SAFETY DATA SHEET GEON M5240 BLACK (T1)

١ R

_

/ersion Number 1.0 Revision Date 11/20/2013	Page 7 of 7 Print Date 11/21/2013
SARA Title III Section 302 Extra	emely Hazardous Substance
Unless specific chemicals are ide	ntified under this section, this product is Not Applicable under this regulation
SARA Title III Section 313 Toxi	c Chemicals:
Unless specific chemicals are ide	ntified under this section, this product is Not Applicable under this regulation
Canadian Regulations:	
National Pollutant Release	e Inventory (NPRI)
not applicable	
WHMIS Classification	: D2A
WHMIS Ingredient Discle	osure List
CAS-No. 1333-86-4]
DSL	: All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.
National Inventories:	
Australia AICS	: Not determined
China IECS	: Not determined
Europe EINECS	: Listed
Japan ENCS	: Not determined
Korea KECI	: Not determined
Philippines PICCS	: Not determined
	16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.