PolvOne

MATERIAL SAFETY DATA SHEET 150-303-079-04

Version Number 1.0 Revision Date 12/02/2013

Product Use

Page 1 of 8 Print Date 12/2/2013

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

| Telephone Emergency telephone number | : | 1 (440) 930-1000 or 1 (866) POLYONE CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident). |
|--|---|--|
| Product name | : | 150-303-079-04 |
| Product code | : | VC10009731 |
| Chemical Name | : | Mixture |
| CAS-No. | : | Mixture |

: Industrial Applications

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Components | CAS-No. | Weight percent |
|-----------------------|------------|----------------|
| Antimony trioxide | 1309-64-4 | 1 - 5 |
| Titanium dioxide | 13463-67-7 | 1 - 5 |
| Dibutyltin mercaptide | 10584-98-2 | 1 - 5 |

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating or processing. The end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 8 and 11 for special precautions. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.

POTENTIAL HEALTH EFFECTS

| Routes of Exposure: | : Inhalation, Ingestion, Skin contact |
|---------------------|---|
| Acute exposure | |
| Inhalation | : Resin particles, like other inert materials, can be mechanically irritating. |
| Ingestion | : May be harmful if swallowed. |
| Eyes | : Resin particles, like other inert materials, are mechanically irritating to eyes. |
| Skin | : Experience shows no unusual dermatitis hazard from routine handling. |

POLYONE CORPORATION

PolyOne.

MATERIAL SAFETY DATA SHEET **150-303-079-04**

Version Number 1.0 Revision Date 12/02/2013 Page 2 of 8 Print Date 12/2/2013

| Medical Conditions Aggravated by Exposure: | : None known. |
|--|---|
| | 4. FIRST AID MEASURES |
| Inhalation | : Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice. |
| Ingestion | : Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice. |
| Eyes | : Rinse immediately with plenty of water, also under the eyelids, for a least 15 minutes. If eye irritation persists, seek medical attention. |
| Skin | : Wash off with soap and plenty of water. If skin irritation persists seek medical attention. |
| | 5. FIREFIGHTING MEASURES |
| Flash point | : not applicable |
| Flammable Limits Upper explosion limit Lower explosion limit Auto-ignition temperature Suitable extinguishing media Special Fire Fighting Procedures Unusual Fire/Explosion | not applicable not applicable Not applicable Carbon dioxide blanket, Water spray, Dry powder, Foam. Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) unde fire conditions. Contaminate (CO) |
| Hazards | fire conditions. Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. |
| | 6. ACCIDENTAL RELEASE MEASURES |
| Personal precautions | : Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls. |
| Environmental precautions | : Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil. |
| Methods for cleaning up | : Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. |



MATERIAL SAFETY DATA SHEET **150-303-079-04**

Version Number 1.0 Revision Date 12/02/2013 Page 3 of 8 Print Date 12/2/2013

| Handling | : | Take measures to prevent the build up of electrostatic charge. Heat only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of these materials. |
|-----------------------------------|------|---|
| Storage | : | Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place. |
| 8. EX | POSU | RE CONTROLS/PERSONAL PROTECTION |
| Respiratory protection | : | No personal respiratory protective equipment normally required. If dusty conditions occur wear appropriate respiratory protection. |
| Eye/Face Protection | : | Safety glasses with side-shields |
| Hand protection | : | Protective gloves |
| Skin and body protection | : | Long sleeved clothing |
| Additional Protective Measures | : | Safety shoes |
| General Hygiene Considerations | : | Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). It is unlikely, under normal working conditions with adequate ventilation, that the exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels. |
| Engineering measures | : | Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery. |
| Exposure limit(s) | | |

<u>PolyOne</u>

MATERIAL SAFETY DATA SHEET **150-303-079-04**

Version Number 1.0 Revision Date 12/02/2013 Page 4 of 8 Print Date 12/2/2013

| Components | Value | Exposure time | Exposure type | List: |
|-----------------------|-----------|--------------------------------------|---------------|----------|
| Antimony trioxide | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | MX OEL |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | ACGIH |
| | 0.5 mg/m3 | Recommended exposure limit (REL): | as Sb | NIOSH |
| | 0.5 mg/m3 | PEL: | as Sb | OSHA Z1 |
| | 0.5 mg/m3 | Time Weighted Average (TWA): | as Sb | OSHA Z1A |
| Titanium dioxide | 10 mg/m3 | Time Weighted Average (TWA): | | ACGIH |
| | 15 mg/m3 | PEL: | Total dust. | OSHA Z1 |
| | 10 mg/m3 | Time Weighted Average (TWA): | Total dust. | OSHA Z1A |
| | 10 mg/m3 | Time Weighted Average (TWA): | as Ti | MX OEL |
| | 20 mg/m3 | Short Term Exposure Limit (STEL): | as Ti | MX OEL |
| Dibutyltin mercaptide | 0.1 mg/m3 | Time Weighted Average (TWA): | as Sn | ACGIH |
| | 0.2 mg/m3 | Short Term Exposure Limit (STEL): | as Sn | ACGIH |
| | 0.1 mg/m3 | PEL: | as Sn | OSHA Z1 |
| | 0.1 mg/m3 | Time Weighted Average (TWA): | as Sn | MX OEL |
| | 0.2 mg/m3 | Short Term Exposure Limit (STEL): | as Sn | MX OEL |

9. PHYSICAL AND CHEMICAL PROPERTIES

Form Appearance Colour Odour Melting point/range Boiling Point: Water solubility solid
pellets, powder
NO PIGMENT
very faint
Not determined
not applicable
insoluble

Evapouration rate Specific Gravity Bulk density Vapour pressure Vapour density pH

Not applicable
Not determined
Not established
not applicable
not applicable
not applicable

10. STABILITY AND REACTIVITY

| Stability | : | The product is stable if stored and handled as prescribed. |
|--------------------------|---|--|
| Hazardous Polymerization | : | Will not occur. |
| Conditions to avoid | : | Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat. |
| Incompatible Materials | : | Incompatible with strong acids and oxidizing agents., Avoid contact |

POLYONE CORPORATION



MATERIAL SAFETY DATA SHEET **150-303-079-04**

Version Number 1.0 Revision Date 12/02/2013 Page 5 of 8 Print Date 12/2/2013

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition
products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen
(NOx), other hazardous materials, and smoke are all possible.
Prolonged heating (approximately 30 minutes or more) above 392 °F
(200 °C) or short term heating at 482 °F (250 °C) may result in
product decomposition and evolution of carbon monoxide and
hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

| CAS-No. | Chemical Name | Effect | Target Organ |
|------------|-----------------------|------------------|---------------------------|
| 1309-64-4 | Antimony trioxide | Systemic effects | Eyes, Respiratory system. |
| | | sensitizer | Skin. |
| 13463-67-7 | Titanium dioxide | Systemic effects | Respiratory system. |
| 10584-98-2 | Dibutyltin mercaptide | Irritant | Eyes, Skin. |

LC50 / LD50

This product contains the following components which, in their pure form, have the following toxicity data:

| CAS-No. | Chemical Name | Route | Value | Species |
|-----------|-------------------|-----------|----------------|---------|
| 1309-64-4 | Antimony trioxide | Oral LD50 | > 34,600 mg/kg | rat |

Carcinogenicity

This product contains the following components which, in their pure form, have the following carcinogenicity data:

| CAS-No. | Chemical Name | OSHA | IARC | NTP |
|------------|-------------------|------|------|-----|
| 1309-64-4 | Antimony trioxide | no | 2B | no |
| 13463-67-7 | Titanium dioxide | no | 2B | no |

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

PolyOne.

MATERIAL SAFETY DATA SHEET **150-303-079-04**

Version Number 1.0 Revision Date 12/02/2013 Page 6 of 8 Print Date 12/2/2013

| | 12. ECOLOGICAL INFORMATION |
|-------------------------------|---|
| Persistence and degradability | : Not readily biodegradable. |
| Environmental Toxicity | : Adverse ecological impact is not known or expected under normal use. |
| Bioaccumulation Potential | : no data available |
| Additional advice | : not applicable |
| | 13. DISPOSAL CONSIDERATIONS |
| Product | : Like most thermoplastic plastics the product can be recycled. Where possible recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| Contaminated packaging | : Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations. |
| | 14. TRANSPORT INFORMATION |
| U.S. DOT Classification | : Not regulated for transportation. |
| ICAO/IATA | : Not regulated for transportation. |
| IMO/IMDG (maritime) | : Not regulated for transportation. |
| | 15. REGULATORY INFORMATION |
| US Regulations: | |
| OSHA Status | : Classified as hazardous based on components. |
| TSCA Status | : All components of this product are listed on or exempt from the TSCA Inventory. |
| US. EPA CERCLA Hazardous | Substances (40 CFR 302) |
| not applicable | |
| California Proposition | : WARNING! This product contains a chemical known to the State o |

MATERIAL SAFETY DATA SHEET 150-303-079-04

Version Number 1.0 Revision Date 12/02/2013 Page 7 of 8 Print Date 12/2/2013

65

California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

SARA Title III Section 313 Toxic Chemicals:

Unless specific chemicals are identified under this section, this product is Not Applicable under this regulation

| Chemical Name | CAS-NO. | weight percent |
|--------------------|-----------|----------------|
| ANTIMONY COMPOUNDS | 1309-64-4 | 1.00 - 5.00 |
| | | |

Canadian Regulations:

National Pollutant Release Inventory (NPRI)Chemical NameCAS-No.Weight
percentNPRI ID#
percentAntimony trioxide1309-64-41.00 - 5.00Molybdenum zinc oxide (Mo2Zn3O9)22914-58-50.10 - 1.00

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

| CAS-No. | |
|------------|--|
| 1309-64-4 | |
| 10584-98-2 | |

DSL

All components of this product are on the Canadian Domestic Substances List (DSL) or are exempt.

National Inventories:

| Australia AICS | : | Not determined |
|-------------------|---|----------------|
| China IECS | : | Not determined |
| Europe EINECS | : | Not determined |
| Japan ENCS | : | Not determined |
| Korea KECI | : | Not determined |
| Philippines PICCS | : | Not determined |

÷

PolyOne

MATERIAL SAFETY DATA SHEET **150-303-079-04**

Version Number 1.0 Revision Date 12/02/2013 Page 8 of 8 Print Date 12/2/2013

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.