

MATERIAL SAFETY DATA SHEET

# EXP X11115406803NAT

Version Number 1.0 Revision Date 04/16/2002 Page 1 of 6 Print Date 11/4/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	EXP X11115406803NAT
Product code	:	X11115406803
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Titanium dioxide	13463-67-7	0.1 - 1
Antimony trioxide	1309-64-4	1 - 5

# **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that OSHA exposure levels will be exceeded for residual VCM. However, it is recommended that the user take necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

# EXP X11115406803NAT

Version Number 1.0 Revision Date 04/16/2002 Page 2 of 6 Print Date 11/4/2011

Medical Conditions	: None known.
Aggravated by Exposure:	
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists seel medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable.</li> <li>water, dry powder, foam, carbon dioxide (CO2).</li> </ul>
Special Fire Fighting Procedures	<ul> <li>Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.</li> <li>May amit Hudggen Chlorida (UCl) or Carbon Manavida (CO) under</li> </ul>
Unusual Fire/Explosion Hazards	: May emit Hydogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

2/6



### MATERIAL SAFETY DATA SHEET

# EXP X11115406803NAT

sion Number 1.0 ision Date 04/16/2002			Pri	Page 3 int Date 11/4/2
Handling	or cc cl	nly in areas with appropriation of the second se	ne build up of electrostation ate exhaust ventilation. P ombustible or toxic residu er surfaces to minimize ac	rocessing fume e. Periodically
Storage		eep containers dry and tig d contamination. Keep in	htly closed to avoid mois n a dry, cool place.	ture absorption
8. I	EXPOSURE	CONTROLS / PERSON	AL PROTECTION	
Respiratory protection	: N	o personal respiratory pro	tective equipment normal	lly required.
Eye/Face Protection	: Sa	afety glasses with side-shi	elds.	
Hand protection	: Pr	otective gloves.		
Skin and body protection	: Lo	ong sleeved clothing.		
Additional Protective Measures	: Sa	afety shoes.		
General Hygiene Considerations			good industrial hygiene an and at the end of workday	
Engineering measures		eat only in areas with app propriate exhaust ventilat	ropriate exhaust ventilation at machinery.	on. Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:	as Sb	OSHA Z1
	9. PHYSIC	CAL AND CHEMICAL	PROPERTIES	
Form Appearance Color Odor Maling point/space	: NO P : Very	ts, powder Sp PIGMENT Bu faint Va	becific Gravity:Ik density:Apor pressure:I	Not applicable. Not determined Not established Not applicable
Melting point/range Boiling Point:		letermined Va pplicable pH		Not applicable Not applicable
Water solubility	: Insolu	uble		
	10. S	TABILITY AND REAC	CTIVITY	
Stability	: St	able.		
Hazardous Polymerization	n : W	fill not occur.		



#### MATERIAL SAFETY DATA SHEET

# EXP X11115406803NAT

Conditions to avoid: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.Incompatible Materials: Incompatible with strong acids and oxidizing agents.Hazardous decomposition products: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride	Version Number 1.0 Revision Date 04/16/2002		Page 4 of 6 Print Date <i>11/4/2011</i>
Hazardous decomposition products:Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and	Conditions to avoid	:	
products (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and	Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
nydrogen emoride.	1	:	(NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may

#### **11. TOXICOLOGICAL INFORMATION**

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

### Additional Health Hazard Information:



MATERIAL SAFETY DATA SHEET

# EXP X11115406803NAT

Version Number 1.0 Revision Date 04/16/2002 Page 5 of 6 Print Date 11/4/2011

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

	12. ECOLOGICAL	INFORMATION	
Persistence and degradability	: Not readily biodeg	gradable.	
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.		
Bioaccumulation Potential	: No data available.		
Additional advice	: Not applicable		
	13. DISPOSAL CON	NSIDERATIONS	
Product	possible, recycling generator of waste classification, tran	plastics the product can be recycled. Where is preferred to disposal or incineration. The material has the responsibility for proper waste sportation and disposal in accordance with state/provincial and local regulations.	
Contaminated packaging	has the responsibil	rred when possible. The generator of waste materia ity for proper waste classification, transportation cordance with applicable federal, state/provincial ns.	
	14. TRANSPORT I	NFORMATION	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for t	ransportation.	
ICAO/IATA	: Not regulated for t	ransportation.	
IMO / IMDG	: Not regulated for t	ransportation.	
	15. REGULATORY	INFORMATION	
US Regulations:			
OSHA Status	: Classified as haza	dous based on components.	
TSCA Status	: All components of exempt.	this product are listed on the TSCA inventory or are	
US. EPA CERCLA Hazardous	Substances (40 CFR 30)	2)	
CD: EITT CEITCEITTIGEdit Gous			



#### MATERIAL SAFETY DATA SHEET

# EXP X11115406803NAT

Version Number 1.0 Revision Date 04/16/2002 Page 6 of 6 Print Date 11/4/2011

California Proposition : 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	1.98

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1309-64-4
544-63-8
112-80-1
57-11-4

DSL

: Listed.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

#### **16. OTHER INFORMATION**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.