

#### MATERIAL SAFETY DATA SHEET

# EXP V0022G CAMPINE ANTIMONY OXIDE

 Version Number 1.0
 Page 1 of 7

 Revision Date 01/27/2003
 Print Date 11/10/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION

33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY : Product Stewardship (440)-930-1395

TELEPHONE

Emergency telephone : CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure

number or accident).

Product name : EXP V0022G CAMPINE ANTIMONY OXIDE

Product code : X15023303001

Chemical Name : Mixture CAS-No. : Mixture

Product Use : Industrial Applications

# 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Decabromodiphenyl oxide	1163-19-5	30 - 60
Arsenic	7440-38-2	0.1 - 1
Antimony trioxide	1309-64-4	10 - 30

# 3. HAZARDS IDENTIFICATION

### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that the OSHA action level and the OSHA exposure limits will be exceeded for residual VCM. However, the user should take the necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

#### POTENTIAL HEALTH EFFECTS

**Routes of Exposure:** : Inhalation, Ingestion, Skin contact

Acute exposure

Inhalation : Resin particles, like other inert materials, can be mechanically irritating.

Ingestion : May be harmful if swallowed.

Eyes : Resin particles, like other inert materials, are mechanically irritating to

eyes.

Skin : Experience shows no unusual dermatitis hazard from routine handling.



#### MATERIAL SAFETY DATA SHEET

# EXP V0022G CAMPINE ANTIMONY OXIDE

Version Number 1.0 Page 2 of 7 Revision Date 01/27/2003 Print Date 11/10/2011

Chronic exposure : Refer to Section 11 for Toxicological Information.

**Medical Conditions** 

**Aggravated by Exposure:** 

: None known.

4. FIRST AID MEASURES

Inhalation Move to fresh air in case of accidental inhalation of fumes from

overheating or combustion. When symptoms persist or in all cases of

doubt seek medical advice.

Do not induce vomiting without medical advice. When symptoms Ingestion

persist or in all cases of doubt seek medical advice.

Eyes : Rinse immediately with plenty of water, also under the eyelids, for at

least 15 minutes. If eye irritation persists, seek medical attention.

Skin Wash off with soap and plenty of water. If skin irritation persists seek

medical attention.

5. FIRE-FIGHTING MEASURES

Flash point : Not applicable

Flammable Limits

Upper explosion limit Not applicable Lower explosion limit Not applicable Autoignition temperature Not applicable.

Suitable extinguishing media water, dry powder, foam, carbon dioxide (CO2).

Special Fire Fighting

Procedures

: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne

contaminants.

Unusual Fire/Explosion

Hazards

May emit Hydrogen Chloride (HCl) or Carbon Monoxide (CO) under

fire conditions.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear appropriate personal protection during cleanup, such as

impervious gloves, boots and coveralls.

Should not be released into the environment. The product should not Environmental precautions

be allowed to enter drains, water courses or the soil.

Methods for cleaning up Clean up promptly by sweeping or vacuum. Package all material in

plastic, cardboard or metal containers for disposal. Refer to Section 13

of this MSDS for proper disposal methods.



#### MATERIAL SAFETY DATA SHEET

# EXP V0022G CAMPINE ANTIMONY OXIDE

 Version Number 1.0
 Page 3 of 7

 Revision Date 01/27/2003
 Print Date 11/10/2011

### 7. HANDLING AND STORAGE

Handling : Take measures to prevent the build up of electrostatic charge. Heat

only in areas with appropriate exhaust ventilation. Processing fume condensates may contain combustible or toxic residue. Periodically clean hoods, ducts, and other surfaces to minimize accumulation of

these materials.

Storage : Keep containers dry and tightly closed to avoid moisture absorption

and contamination. Keep in a dry, cool place.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Respiratory protection : No personal respiratory protective equipment normally required.

Eye/Face Protection : Safety glasses with side-shields.

Hand protection : Protective gloves.

Skin and body protection : Long sleeved clothing.

Additional Protective

Measures

: Safety shoes.

: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Engineering measures : Heat only in areas with appropriate exhaust ventilation. Provide

appropriate exhaust ventilation at machinery.

### Exposure limit(s)

General Hygiene

Considerations

Components	Value	Exposure time	Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:	as Sb	OSHA Z1
Arsenic	0.01	Time Weighted Average	as As	ACGIH
	mg/m3	(TWA):		
Arsenic	0.01	Time Weighted Average	as As	OSHA
	mg/m3	(TWA):		

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Evaporation rate Not applicable. Form : Solid Not determined Appearance : Pellets, powder Specific Gravity : NOT APPLICABLE : Not established Color Bulk density Odor : Very faint Vapor pressure : Not applicable : Not applicable Melting point/range : Not determined Vapor density **Boiling Point:** : Not applicable : Not applicable pН

Water solubility : Insoluble



#### MATERIAL SAFETY DATA SHEET

# EXP V0022G CAMPINE ANTIMONY OXIDE

Version Number 1.0 Page 4 of 7
Revision Date 01/27/2003 Print Date 11/10/2011

#### 10. STABILITY AND REACTIVITY

Stability : Stable.

Hazardous Polymerization : Will not occur.

Conditions to avoid : Keep away from oxidizing agents and open flame. To avoid thermal

decomposition, do not overheat.

Incompatible Materials : Incompatible with strong acids and oxidizing agents. Avoid contact

with acetal homopolymers and acetal copolymers during processing.

Hazardous decomposition

products

: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen

(NOx), other hazardous materials, and smoke are all possible.

Prolonged heating (approximately 30 minutes or more) above 392  $^{\circ}$ F (200  $^{\circ}$ C) or short term heating at 482  $^{\circ}$ F (250  $^{\circ}$ C) may result in product decomposition and evolution of carbon monoxide and hydrogen

chloride.

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### **Toxicity Overview**

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1163-19-5	Decabromodiphenyl oxide	Systemic effects	Liver, Kidney.
7440-38-2	Arsenic	Systemic effects	Skin, Respiratory system, Liver, Kidney, heart or circulatory system.
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

#### LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1163-19-5	Decabromodiphenyl oxide	Oral LD50	> 5 gm/kg	rat
7440-38-2	Arsenic	Oral LD50	763 mg/kg	rat
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

#### Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
7440-38-2	Arsenic	yes	1	1



#### MATERIAL SAFETY DATA SHEET

# EXP V0022G CAMPINE ANTIMONY OXIDE

 Version Number 1.0
 Page 5 of 7

 Revision Date 01/27/2003
 Print Date 11/10/2011

1309-64-4	Antimony trioxide	no	2B	no
-----------	-------------------	----	----	----

#### IARC Carcinogen Classifications:

- 1 The component is carcinogenic to humans.
- 2A The component is probably carcinogenic to humans.
- 2B The component is possibly carcinogenic to humans.

#### NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

#### **Additional Health Hazard Information:**

Decabromodiphenyl oxide 1163-19-5 A halogenated aromatic with some potential for hazardous exposure via inhalation or ingestion. Acute toxicity is low - oral LD50 in rats >50 mg/L. Animal studies at high feeding levels indicate some potential for liver effects form chronic overexposure.

### **Additional Health Hazard Information:**

Arsenic 7440-38-2 Trivalent compounds are corrosive to skin. Acute effects are due to severe inflammation of mucous membrane while chronic effects include peripheral neuritis, perforation for the nasal septum and mild tracheobronchitis.

# **Additional Health Hazard Information:**

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).

12. ECOLOGICAL INFORMATION
: Not readily biodegradable.
: Adverse ecological impact is not known or expected under normal use.
: No data available.
: Not applicable
13. DISPOSAL CONSIDERATIONS
: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.



# MATERIAL SAFETY DATA SHEET

# **EXP V0022G CAMPINE ANTIMONY OXIDE**

 Version Number 1.0
 Page 6 of 7

 Revision Date 01/27/2003
 Print Date 11/10/2011

U.S. DOT Classification : Not regulated for transportation.

ICAO/IATA : Not regulated for transportation.

IMO / IMDG : Not regulated for transportation.

### 15. REGULATORY INFORMATION

US Regulations:

OSHA Status : Classified as hazardous based on components.

TSCA Status : All components of this product are listed on or exempt from the TSCA

Inventory.

US. EPA CERCLA Hazardous Substances (40 CFR 302)

Chemical Name	CAS-No.	% in Product	RQ for component	RQ for
				Mixture/Product
Arsenic	7440-38-2	0.1032	001 lbs	969 LB

California Proposition : WARNING! This product contains a chemical known to the State of

California to cause cancer.

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	25.70
ARSENIC	7440-38-2	00.10
DECABROMODIPHENYL OXIDE	1163-19-5	43.86

### Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
1309-64-4
7440-38-2

DSL : All components of this product are on the Canadian Domestic



### MATERIAL SAFETY DATA SHEET

# **EXP V0022G CAMPINE ANTIMONY OXIDE**

Version Number 1.0 Page 7 of 7
Revision Date 01/27/2003 Print Date 11/10/2011

Substances List (DSL) or are exempt.

National Inventories:

Australia AICS : Listed.

China IECS : Listed.

Europe EINECS : Not determined.

Japan ENCS : Not determined.

Korea KECI : Not determined.

Philippines PICCS : Listed.

# 16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.