

MATERIAL SAFETY DATA SHEET

EXP CP 15502101510 VIOLET

Version Number 1.0 Revision Date 04/16/2002 Page 1 of 7 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	EXP CP 15502101510 VIOLET
Product code	:	X15502101510
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Antimony trioxide	1309-64-4	1 - 5

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that OSHA exposure levels will be exceeded for residual VCM. However, it is recommended that the user take necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

EXP CP 15502101510 VIOLET

sion Date 04/16/2002	Print Date 11/4/2
Chronic exposure	: Refer to Section 11 for Toxicological Information.
Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases o doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 Not applicable Not applicable Not applicable. water, dry powder, foam, carbon dioxide (CO2).
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	 May emit Hydogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE



MATERIAL SAFETY DATA SHEET

EXP CP 15502101510 VIOLET

sion Date 04/16/2002					nt Date 11/4/2
Handling	0 C C	Take measures to prevonly in areas with app ondensates may cont lean hoods, ducts, an hese materials.	ropriate exhaus ain combustible	st ventilation. Pro	ocessing fume . Periodically
Storage		Keep containers dry and tightly closed to avoid moisture absorption and contamination. Keep in a dry, cool place.			
8. I	EXPOSURE	CONTROLS / PER	RSONAL PRO	TECTION	
Respiratory protection	: N	No personal respirator	ry protective eq	uipment normall	y required.
Eye/Face Protection	: \$	afety glasses with sid	le-shields.		
Hand protection	: F	Protective gloves.			
Skin and body protection	: I	ong sleeved clothing			
Additional Protective Measures	: S	afety shoes.			
General Hygiene Considerations		Handle in accordance Vash hands before br			l safety practice
Engineering measures		Ieat only in areas wit ppropriate exhaust ve			n. Provide
Exposure limit(s)					
Components	Value	Exposure tin	ne	Exposure type	List:
Antimony trioxide	0.5 mg/m3	PEL:		as Sb	OSHA Z1
				TIFC	
	9. PH 151	CAL AND CHEMI	CAL PROPER		
Form Appearance Color Odor Melting point/range Boiling Point: Water solubility	: PUR : Very : Not	ets, powder PLE / faint determined applicable	Evaporatior Specific Gra Bulk density Vapor press Vapor density pH	avity : N y : N sure : N ity : N	ot applicable. ot determined ot established ot applicable ot applicable ot applicable
	10.	STABILITY AND R	REACTIVITY		
Stability	: \$	table.			
Stability					
Hazardous Polymerization	n : V	Vill not occur.			



MATERIAL SAFETY DATA SHEET

EXP CP 15502101510 VIOLET

Version Number 1.0 Revision Date 04/16/2002		Page 4 of 7 Print Date <i>11/4/2011</i>
Conditions to avoid	:	Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	:	Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	:	Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible. Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.

11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
1309-64-4	Antimony trioxide	Systemic effects	Eyes, Respiratory system.
		sensitizer	Skin.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
1309-64-4	Antimony trioxide	Oral LD50	> 34,600 mg/kg	rat

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
1309-64-4	Antimony trioxide	no	2B	no

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.

NTP Carcinogen Classifications:

- 1 The component is known to be a human carcinogen.
- 2 The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Antimony trioxide 1309-64-4 Can cause eye irritation. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Additional symptoms of skin contact may include: antimony measles (a red, pimply rash).



MATERIAL SAFETY DATA SHEET

EXP CP 15502101510 VIOLET

Version Number 1.0 Revision Date 04/16/2002 Page 5 of 7 Print Date 11/4/2011

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: No data available.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
TSCA Status	: All components of this product are listed on the TSCA inventory or an exempt.
California Proposition 65	: WARNING! This product contains a chemical known in the State of California to cause cancer., WARNING! This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.
CADA T:41. III Continue 202 En	tremely Hazardous Substance



MATERIAL SAFETY DATA SHEET

EXP CP 15502101510 VIOLET

Version Number 1.0 Revision Date 04/16/2002 Page 6 of 7 Print Date 11/4/2011

Chemical Name	CAS-No.	RQ for component
10,10'-Oxybisphenoxarsine	58-36-6	500 lbs

SARA Title III Section 313 Toxic Chemicals:

Chemical Name	CAS-No.	Weight %
ANTIMONY COMPOUNDS	1309-64-4	3.99

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.	
1309-64-4	
112-34-5	
7439-92-1	
7439-97-6	
101-02-0	
151-21-3	
2457-01-4	
28987-17-9	

National Inventories:

DSL

Australia AICS	: Listed.
China IECS	: Not determined.
Europe EINECS	: Not determined.
Japan ENCS	: Not determined.
Korea KECI	: Listed.
Philippines PICCS	: Listed.

: Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.



MATERIAL SAFETY DATA SHEET

EXP CP 15502101510 VIOLET

Version Number 1.0 Revision Date 04/16/2002 Page 7 of 7 Print Date 11/4/2011