

MATERIAL SAFETY DATA SHEET

EXP 15502304301WHT

Version Number 1.0 Revision Date 04/18/2002 Page 1 of 6 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	EXP 15502304301WHT
Product code	:	X15502304301
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Quartz	14808-60-7	0.1 - 1
Titanium dioxide	13463-67-7	1 - 5
Calcium carbonate	1317-65-3	10 - 30

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that OSHA exposure levels will be exceeded for residual VCM. However, it is recommended that the user take necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation Ingestion Eyes	 Resin particles, like other inert materials, can be mechanically irritating. May be harmful if swallowed. Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

EXP 15502304301WHT

Version Number 1.0 Revision Date 04/18/2002 Page 2 of 6 Print Date 11/4/2011

Medical Conditions : None known. Aggravated by Exposure:			
		4. FIRST AID MEASURES	
Inhalation	:	Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases of doubt seek medical advice.	
Ingestion	:	Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.	
Eyes	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.	
Skin	:	Wash off with soap and plenty of water. If skin irritation persists seek medical attention.	
		5. FIRE-FIGHTING MEASURES	
Flash point	:	Not applicable	
Flammable Limits			
Upper explosion limit	:	Not applicable	
Lower explosion limit	:	Not applicable	
Autoignition temperature	:	Not applicable.	
Suitable extinguishing media	:	water, dry powder, foam, carbon dioxide (CO2).	
Special Fire Fighting	:	Fullface self-contained breathing apparatus (SCBA) used in positive	
Procedures		pressure mode should be worn to prevent inhalation of airborne	
		contaminants.	
Unusual Fire/Explosion Hazards	:	May emit Hydogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.	
	6. A	CCIDENTAL RELEASE MEASURES	
Personal precautions	:	Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.	
Environmental precautions	:	Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.	
Methods for cleaning up	:	Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 13 of this MSDS for proper disposal methods.	



MATERIAL SAFETY DATA SHEET

EXP 15502304301WHT

sion Date 04/18/2002			Print	Date 11/4/
	7.	HANDLING AND STORAG	E	
Handling		ake measures to prevent the bundly in areas with appropriate exondensates may contain combunean hoods, ducts, and other surfaces materials.	haust ventilation. Prod stible or toxic residue.	cessing fume Periodically
Storage		eep containers dry and tightly and contamination. Keep in a dr		e absorption
8. I	EXPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: N	o personal respiratory protectiv	ve equipment normally	required.
Eye/Face Protection	: S	afety glasses with side-shields.		
Hand protection	: P	rotective gloves.		
Skin and body protection	: L	ong sleeved clothing.		
Additional Protective Measures	: S	afety shoes.		
General Hygiene Considerations		andle in accordance with good /ash hands before breaks and a		safety practic
Engineering measures		eat only in areas with appropri ppropriate exhaust ventilation a		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Calcium carbonate	5 mg/m3	PEL:	Respirable dust.	OSHA Z
	15 mg/m3	PEL:	Total dust.	OSHA Z
Quartz	0.05 mg/m3	Time Weighted Average (TWA):	Respirable dust.	ACGIH
Quartz	0.1 mg/m3	PEL:	Respirable dust.	OSHA
Titonium 1's 11	0.3 mg/m3	PEL:	Total dust.	OSHA
Titanium dioxide	10 mg/m3	Time Weighted Average (TWA):	Total dust.	ACGIH
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z
	9. PHYSIC	CAL AND CHEMICAL PRO	PERTIES	
Form	: Solid	l Evapor	ation rate : No	t applicable.



MATERIAL SAFETY DATA SHEET

EXP 15502304301WHT

ersion Number 1.0 evision Date 04/18/2002			Page 4 o Print Date 11/4/20
Appearance Color Odor Melting point/range Boiling Point: Water solubility	 Pellets, powder WHITE Very faint Not determined Not applicable Insoluble 	Specific Gravity Bulk density Vapor pressure Vapor density pH	
	10. STABILITY AND I	REACTIVITY	
Stability	: Stable.		
Hazardous Polymerization	: Will not occur.		
Conditions to avoid	: Keep away from oxid decomposition, do no		lame. To avoid thermal
Incompatible Materials	: Incompatible with str	ong acids and oxidizing	agents.
Hazardous decomposition products	(NOx), other hazardo Prolonged heating (ap F (200 deg C) or shor	t term heating at 482 De	are all possible. s or more) above 392 Deg
	11. TOXICOLOGICAL I	NFORMATION	

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
14808-60-7	Quartz	Systemic effects	Eyes, Respiratory system.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.
1317-65-3	Calcium carbonate	Irritant	Eyes, Skin.
		Systemic effects	Eyes, Skin, Respiratory system.

Carcinogenicity:

This product contains the following components which in their pure form have the following carcinogenicity data:

CAS-No.	Chemical Name	OSHA	IARC	NTP
14808-60-7	Quartz	no	1	1

IARC Carcinogen Classifications:

1 - The component is carcinogenic to humans.

2A - The component is probably carcinogenic to humans.

2B - The component is possibly carcinogenic to humans.



MATERIAL SAFETY DATA SHEET

EXP 15502304301WHT

Version Number 1.0 Revision Date 04/18/2002 Page 5 of 6 Print Date 11/4/2011

NTP Carcinogen Classifications:

1 - The component is known to be a human carcinogen.

2 - The component is reasonably anticipated to be a human carcinogen.

Additional Health Hazard Information:

Quartz 14808-60-7 This material in its free releasable form may cause respiratory tract irritation, and possibly silicosis which is a scarring of the lungs.

12. ECOLOGICAL INFORMATION

Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	: No data available.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: Classified as hazardous based on components.
	: All components of this product are listed on the TSCA inventory or are



MATERIAL SAFETY DATA SHEET

EXP 15502304301WHT

Version Number 1.0 Revision Date 04/18/2002 Page 6 of 6 Print Date 11/4/2011

California Proposition : 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

SARA Title III Section 302 Extremely Hazardous Substance

Chemical Name	CAS-No.	RQ for component
10,10'-Oxybisphenoxarsine	58-36-6	500 lbs

Canadian Regulations:

WHMIS Classification : D2A

WHMIS Ingredient Disclosure List

CAS-No.
544-63-8
112-80-1
14808-60-7
57-11-4
101-02-0

DSL

: Listed.

National Inventories:

Australia AICS	:	Listed.
China IECS	:	Listed.
Europe EINECS	:	Not determined.
Japan ENCS	:	Not determined.
Korea KECI	:	Listed.
Philippines PICCS	:	Listed.

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.