

MATERIAL SAFETY DATA SHEET

# EXP 15504004308WHT

Version Number 1.0 Revision Date 04/19/2002 Page 1 of 6 Print Date 11/4/2011

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY TELEPHONE	:	Product Stewardship (440)-930-1395
Emergency telephone number	:	CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).
Product name	:	EXP 15504004308WHT
Product code	:	X15504004308
Chemical Name	:	Mixture
CAS-No.	:	Mixture
Product Use	:	Industrial Applications

#### 2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

Components	CAS-No.	Weight %
Calcium carbonate	471-34-1	1 - 5
Titanium dioxide	13463-67-7	1 - 5

### **3. HAZARDS IDENTIFICATION**

#### **EMERGENCY OVERVIEW**

This mixture has not been evaluated as a whole for health effects. Information provided on health effects of this product is based on the individual components. See Sections 3 and 11 for additional details. This product may contain residual vinyl chloride monomer (VCM) (CAS number 75-01-4) below 8.5 ppm (0.00085%). OSHA considers VCM a suspect carcinogen and regulates it under 29 CFR 1910.1017. It is unlikely, under normal working conditions with adequate ventilation, that OSHA exposure levels will be exceeded for residual VCM. However, it is recommended that the user take necessary precautions (e.g. mechanical ventilation, local exhaust ventilation, air-monitoring, respiratory protection, etc.) to ensure airborne levels of any vapors including VCM or dusts that may be released during heating or processing are below regulated levels.

#### POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Ingestion, Skin contact
Acute exposure	
Inhalation	: Resin particles, like other inert materials, can be mechanically irritating.
Ingestion	: May be harmful if swallowed.
Eyes	: Resin particles, like other inert materials, are mechanically irritating to eyes.
Skin	: Experience shows no unusual dermatitis hazard from routine handling.



MATERIAL SAFETY DATA SHEET

# EXP 15504004308WHT

Version Number 1.0 Revision Date 04/19/2002 Page 2 of 6 Print Date 11/4/2011

Medical Conditions Aggravated by Exposure:	: None known.
	4. FIRST AID MEASURES
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. When symptoms persist or in all cases or doubt seek medical advice.
Ingestion	: Do not induce vomiting without medical advice. When symptoms persist or in all cases of doubt seek medical advice.
Eyes	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If eye irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: Not applicable
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	<ul> <li>Not applicable</li> <li>Not applicable</li> <li>Not applicable.</li> <li>water, dry powder, foam, carbon dioxide (CO2).</li> </ul>
Special Fire Fighting Procedures	: Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants.
Unusual Fire/Explosion Hazards	<ul> <li>May emit Hydogen Chloride (HCl) or Carbon Monoxide (CO) under fire conditions.</li> </ul>
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should not be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Clean up promptly by sweeping or vacuum. Package all material in plastic, cardboard or metal containers for disposal. Refer to Section 1 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE

2/6



### MATERIAL SAFETY DATA SHEET

# EXP 15504004308WHT

rsion Number 1.0 vision Date 04/19/2002			Print I	Page 3 of 6 Date 11/4/2011
Handling		Take measures to prevent the buonly in areas with appropriate excondensates may contain combucter hoods, ducts, and other su hese materials.	xhaust ventilation. Proce stible or toxic residue. I	essing fume Periodically
Storage		Keep containers dry and tightly and contamination. Keep in a d		absorption
8. E	XPOSURE	CONTROLS / PERSONAL	PROTECTION	
Respiratory protection	: 1	No personal respiratory protecti	ve equipment normally r	equired.
Eye/Face Protection	: 5	Safety glasses with side-shields		
Hand protection	: F	Protective gloves.		
Skin and body protection	: I	long sleeved clothing.		
Additional Protective Measures	: 5	Safety shoes.		
General Hygiene Considerations		Handle in accordance with good Wash hands before breaks and a		afety practice.
Engineering measures		Heat only in areas with appropri appropriate exhaust ventilation a		Provide
Exposure limit(s)				
Components	Value	Exposure time	Exposure type	List:

Components	Value	Exposure time	Exposure type	List:
Calcium carbonate	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
	_	(TWA):		
Calcium carbonate	5 mg/m3	PEL:	Respirable fraction.	OSHA Z1
	15 mg/m3	PEL:	Total dust.	OSHA Z1
Titanium dioxide	10 mg/m3	Time Weighted Average	Total dust.	ACGIH
		(TWA):		
Titanium dioxide	15 mg/m3	PEL:	Total dust.	OSHA Z1

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Form
Appearance
Color
Odor
Melting point/range
Boiling Point:
Water solubility

Solid
Pellets, powder
WHITE
Very faint
Not determined
Not applicable
Insoluble

Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH Not applicable.
Not determined
Not established
Not applicable
Not applicable
Not applicable



MATERIAL SAFETY DATA SHEET

# EXP 15504004308WHT

Version Number 1.0 Revision Date 04/19/2002 Page 4 of 6 Print Date 11/4/2011

	10. STABILITY AND REACTIVITY
Stability	: Stable.
Hazardous Polymerization	: Will not occur.
Conditions to avoid	: Keep away from oxidizing agents and open flame. To avoid thermal decomposition, do not overheat.
Incompatible Materials	: Incompatible with strong acids and oxidizing agents.
Hazardous decomposition products	<ul> <li>Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), other hazardous materials, and smoke are all possible.</li> <li>Prolonged heating (approximately 30 minutes or more) above 392 Deg F (200 deg C) or short term heating at 482 Deg F (250 deg C) may result in product decomposition and evolution of carbon monoxide and hydrogen chloride.</li> </ul>

### 11. TOXICOLOGICAL INFORMATION

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

#### Toxicity Overview

This product contains the following components which in their pure form have the following characteristics:

CAS-No.	Chemical Name	Effect	Target Organ
471-34-1	Calcium carbonate	Irritant	Eyes, Skin.
13463-67-7	Titanium dioxide	Systemic effects	Respiratory system.

LC50 / LD50

This product contains the following components which in their pure form have the following toxicity data:

CAS-No.	Chemical Name	Route	Value	Species
471-34-1	Calcium carbonate	Oral LD50	6,450 mg/kg	rat

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use.
Bioaccumulation Potential	: No data available.
Additional advice	: Not applicable
	13. DISPOSAL CONSIDERATIONS
Product	: Like most thermoplastics the product can be recycled. Where



MATERIAL SAFETY DATA SHEET

# EXP 15504004308WHT

Version Number 1.0 Revision Date 04/19/2002	Page 5 Print Date 11/4/2	
	possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	
Contaminated packaging	: Recycling is preferred when possible. The generator of waste materia has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.	ıl
	14. TRANSPORT INFORMATION	
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.	
ICAO/IATA	: Not regulated for transportation.	
IMO / IMDG	: Not regulated for transportation.	
	15. REGULATORY INFORMATION	
US Regulations:		
US Regulations: OSHA Status	: Classified as hazardous based on components.	
-	<ul> <li>Classified as hazardous based on components.</li> <li>All components of this product are listed on the TSCA inventory or ar exempt.</li> </ul>	e
OSHA Status	: All components of this product are listed on the TSCA inventory or ar	
OSHA Status TSCA Status California Proposition	<ul> <li>All components of this product are listed on the TSCA inventory or ar exempt.</li> <li>WARNING! This product contains a chemical known in the State of California to cause cancer.</li> </ul>	
OSHA Status TSCA Status California Proposition 65	<ul> <li>All components of this product are listed on the TSCA inventory or ar exempt.</li> <li>WARNING! This product contains a chemical known in the State of California to cause cancer.</li> </ul>	
OSHA Status TSCA Status California Proposition 65 SARA Title III Section 302 Ext Chemical Name Vinyl acetate	<ul> <li>All components of this product are listed on the TSCA inventory or ar exempt.</li> <li>WARNING! This product contains a chemical known in the State of California to cause cancer.</li> <li>remely Hazardous Substance</li> </ul>	
OSHA Status TSCA Status California Proposition 65 SARA Title III Section 302 Ext Chemical Name	<ul> <li>All components of this product are listed on the TSCA inventory or ar exempt.</li> <li>WARNING! This product contains a chemical known in the State of California to cause cancer.</li> <li>remely Hazardous Substance</li> <li>CAS-No. RQ for component</li> </ul>	
OSHA Status TSCA Status California Proposition 65 SARA Title III Section 302 Ext Chemical Name Vinyl acetate	<ul> <li>All components of this product are listed on the TSCA inventory or ar exempt.</li> <li>WARNING! This product contains a chemical known in the State of California to cause cancer.</li> <li>remely Hazardous Substance</li> </ul>	
OSHA Status TSCA Status California Proposition 65 SARA Title III Section 302 Ext Chemical Name Vinyl acetate Acrylonitrile	<ul> <li>All components of this product are listed on the TSCA inventory or ar exempt.</li> <li>WARNING! This product contains a chemical known in the State of California to cause cancer.</li> <li>remely Hazardous Substance</li> </ul>	

CAS-No.
57583-35-4
1333-86-4
1309-48-4
57583-34-3
57-11-4



### MATERIAL SAFETY DATA SHEET

# EXP 15504004308WHT

Version Number 1.0 Revision Date 04/19/2002

100-42-5 108-05-4 107-13-1 25155-30-0 75-01-4		
DSL	: Listed.	
National Inventories:		
Australia AICS	: Listed.	
China IECS	: Listed.	
Europe EINECS	: Not determined.	
Japan ENCS	: Not determined.	
Korea KECI	: Listed.	
Philippines PICCS	: Listed.	
	16. OTHER INFORMATION	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Page 6 of 6 Print Date 11/4/2011