

MATERIAL SAFETY DATA SHEET

SYNPLAST DOTP GREEN NORMAL

Version Number 1.0 Revision Date 05/17/2002 Page 1 of 5 Print Date 11/4/2011

1. PRODUCT AND COMPANY IDENTIFICATION

POLYONE CORPORATION 33587 Walker Road, Avon Lake, OH 44012

NON-EMERGENCY:TELEPHONEEmergency telephone:number		Product Stewardship (770) 271-5902	
		CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).	
Product name	:	SYNPLAST DOTP GREEN NORMAL	
Product code	:	ZDOTPNGR00	
Chemical Name	:	Dioctyl terephthalate; DOTP	
CAS-No.	:	6422-86-2	
Product Use	:	Industrial Applications	

2. COMPOSITION/INFORMATION ON HAZARDOUS INGREDIENTS

There are no known hazardous components above regulatory thresholds in this product.

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This product has not been evaluated as a whole for health effects. However, some vapors or contaminants may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. See sections 3 and 11 for special precautions.

POTENTIAL HEALTH EFFECTS

Routes of Exposure:	: Inhalation, Skin contact, Ingestion				
Acute exposure					
Inhalation	: Inhalation of airborne droplets may cause irritation of the respiratory tract.				
Ingestion	: May be harmful if swallowed.				
Eyes	: Contact with eyes may cause irritation.				
Skin	: Experience shows no unusual dermatitis hazard from routine handling.				
Chronic exposure	: Refer to Section 11 for Toxicological Information.				
Medical Conditions Aggravated by Exposure:	: None known.				
4. FIRST AID MEASURES					



MATERIAL SAFETY DATA SHEET

SYNPLAST DOTP GREEN NORMAL

sion Date 05/17/2002	Page 2 Print Date 11/4/2
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. Seek medical attention after significant exposure.
Ingestion	: Do not induce vomiting without medical advice. Seek medical attention if necessary.
Eyes	: Rinse immediately with plenty of water for at least 15 minutes. If ey irritation persists, seek medical attention.
Skin	: Wash off with soap and plenty of water. If skin irritation persists see medical attention.
	5. FIRE-FIGHTING MEASURES
Flash point	: 238 °C
Flammable Limits Upper explosion limit Lower explosion limit Autoignition temperature Suitable extinguishing media	 No data available. No data available. 399 °C dry powder, foam, carbon dioxide (CO2), Water spray can be used to cool fire exposed surfaces
Special Fire Fighting Procedures Unusual Fire/Explosion Hazards	 Fullface self-contained breathing apparatus (SCBA) used in positive pressure mode should be worn to prevent inhalation of airborne contaminants. None
	5. ACCIDENTAL RELEASE MEASURES
Personal precautions	: Wear appropriate personal protection during cleanup, such as impervious gloves, boots and coveralls.
Environmental precautions	: Should not be released into the environment. The product should no be allowed to enter drains, water courses or the soil.
Methods for cleaning up	: Soak up with inert absorbent material (e.g. sand, silica gel, acid binde universal binder, sawdust). Package all material in appropriate container for disposal. Refer to Section 13 of this MSDS for proper disposal methods.
	7. HANDLING AND STORAGE
Handling	: Heat only in areas with appropriate exhaust ventilation.
Storage	: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Store in a cool dry place.



MATERIAL SAFETY DATA SHEET

SYNPLAST DOTP GREEN NORMAL

Version Number 1.0 Revision Date 05/17/2002 Page 3 of 5 Print Date 11/4/2011

	POSURE CONT	ROLS / PERS	ONAL PROTECTI	ON		
Respiratory protection	: Under normal handling conditions a respirator is not required.					
Eye/Face Protection	: Safety glasses with side-shields.					
Hand protection	: Protective gloves.					
Skin and body protection	: Long sleeved clothing.					
Additional Protective Measures	: Safety shoes.					
General Hygiene Considerations	: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.					
Engineering measures	: Heat only in areas with appropriate exhaust ventilation. Provide appropriate exhaust ventilation at machinery.					
Exposure limit(s)						
There are no known hozardor			thresholds in this pro	aduat		
There are no known hazardo	us components a	bove regulatory	unesholds in uns pro	Juuct.		
9	. PHYSICAL A	ND CHEMICA	AL PROPERTIES			
			IL I KOI LKIILD			
Form	: liquid			: negligible		
Form Appearance	: liquid : viscous, liq	uid	Evaporation rate Specific Gravity	: negligible : 0.984		
			Evaporation rate			
Appearance	: viscous, liq		Evaporation rate Specific Gravity	: 0.984		
Appearance Color Odor Melting point/range	 viscous, liq TRANSPA Very faint -38°C(-36°) 	RENT	Evaporation rate Specific Gravity Bulk density	: 0.984 : Not applicable. : <1.0 mm Hg @ 21		
Appearance Color Odor Melting point/range Boiling Point:	 viscous, liq TRANSPA Very faint -38°C(-36°] 383 °C 	RENT F) Pour point	Evaporation rate Specific Gravity Bulk density Vapor pressure	: 0.984 : Not applicable. : <1.0 mm Hg @ 21 °C		
Appearance Color Odor Melting point/range	 viscous, liq TRANSPA Very faint -38°C(-36°) 	RENT F) Pour point	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density	: 0.984 : Not applicable. : <1.0 mm Hg @ 21 °C : Not determined		
Appearance Color Odor Melting point/range Boiling Point:	 viscous, liq TRANSPA Very faint -38°C(-36°) 383 °C No data ava 	RENT F) Pour point	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	: 0.984 : Not applicable. : <1.0 mm Hg @ 21 °C : Not determined		
Appearance Color Odor Melting point/range Boiling Point:	 viscous, liq TRANSPA Very faint -38°C(-36°) 383 °C No data ava 	RENT F) Pour point ilable.	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	: 0.984 : Not applicable. : <1.0 mm Hg @ 21 °C : Not determined		
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability	 viscous, liq TRANSPA Very faint -38°C(-36°] 383 °C No data ava 10. STABI	RENT ^{F)} Pour point ilable. LITY AND RE	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	: 0.984 : Not applicable. : <1.0 mm Hg @ 21 °C : Not determined		
Appearance Color Odor Melting point/range Boiling Point: Water solubility	 viscous, liq TRANSPA Very faint -38°C(-36°) 383 °C No data ava 10. STABI Stable. Will not 	RENT ^{F)} Pour point ilable. LITY AND RE occur.	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	: 0.984 : Not applicable. : <1.0 mm Hg @ 21 °C : Not determined : Not applicable.		
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization	 viscous, liq TRANSPA Very faint -38°C(-36°) 383 °C No data ava 10. STABI Stable. Will not Keep away 	RENT F) Pour point ilable. LITY AND RE occur. ay from oxidizi	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH	: 0.984 : Not applicable. : <1.0 mm Hg @ 21 °C : Not determined : Not applicable.		
Appearance Color Odor Melting point/range Boiling Point: Water solubility Stability Hazardous Polymerization Conditions to avoid	 viscous, liq TRANSPA Very faint -38°C(-36°] 383 °C No data ava 10. STABI Stable. Will not Keep aw Incompa Carbon 	RENT F) Pour point ilable. LITY AND RE occur. vay from oxidizi tible with strong dioxide (CO2), o	Evaporation rate Specific Gravity Bulk density Vapor pressure Vapor density pH EACTIVITY	 : 0.984 : Not applicable. : <1.0 mm Hg @ 21 °C : Not determined : Not applicable. 		



MATERIAL SAFETY DATA SHEET

SYNPLAST DOTP GREEN NORMAL

Version Number 1.0 Revision Date 05/17/2002 Page 4 of 5 Print Date 11/4/2011

There are no known hazardous components above regulatory thresholds in this product.

	12. ECOLOGICAL INFORMATION
Persistence and degradability	: Not readily biodegradable.
Environmental Toxicity	: Adverse ecological impact is not known or expected under normal use
Bioaccumulation Potential	: Does not bioaccumulate
Additional advice	: No data available.
	13. DISPOSAL CONSIDERATIONS
Product	: Where possible, recycling is preferred to disposal or incineration. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
Contaminated packaging	: Recycling is preferred when possible. The generator of waste material has the responsibility for proper waste classification, transportation and disposal in accordance with applicable federal, state/provincial and local regulations.
	14. TRANSPORT INFORMATION
U.S. D.O.T. / CA T.D.G. Classification (Non-bulk ground)	: Not regulated for transportation.
ICAO/IATA	: Not regulated for transportation.
IMO / IMDG	: Not regulated for transportation.
	15. REGULATORY INFORMATION
US Regulations:	
OSHA Status	: There are no known hazardous components above regulatory thresholds in this product.
TSCA Status	: All components of this product are listed on the TSCA inventory or are exempt.
California Proposition 65	: This product does not contain a substance listed by California Prop 65
Canadian Regulations:	
Callaulali Regulations.	



MATERIAL SAFETY DATA SHEET

SYNPLAST DOTP GREEN NORMAL

Version Number 1.0 Revision Date 05/17/2002 Page 5 of 5 Print Date 11/4/2011

:	Listed.
:	Listed.
	: : : : : : : : : : : : : : : : : : : :

16. OTHER INFORMATION

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.